PHASE I MIDFILED AVENUE BUILDING ACOUSTICAL STUDY

30 Homes West of I-405 Between La Tijera Boulevard and Florence Avenue

LOS ANGELES COUNTY, CALIFORNIA KP 37.7/38.5 (PM 23.4/23.9) EA 07-1198U3

Prepared for:



California Department of Transportation District 7 100 South Main Street Los Angeles, California 90012

May 26, 2005

Prepared by:



100 West Walnut Street, Pasadena, California 91124

PHASE I MIDFILED AVENUE BUILDING ACOUSTICAL STUDY 30 Homes West of I-405 Between La Tijera Boulevard and Florence Avenue

Los Angeles, California KP 37.7/38.5 (PM 23.4/23.9) EA 07-1198U3

Prepared for:
California Department of Transportation District 11
100 South Main Street
Los Angeles, Califoria, 90012

May 26, 2005 645080.03000

Prepared by:



100 West Walnut Street, Pasadena, California 91124

Prepared By:	must M. I sattle	5/20/05
	Emery W. Tuttle	Date
		Market
Reviewed By:	Company of the second	5/26/03
	Areg Charabegian, P.E.	Date

TABLE OF CONTENTS

		PAGE
EXE	ECUTIVE SUMMARY	iii
1.0	INTRODUCTION	1
2.0	PROJECT DESCRIPTION	1
3.0	FUNDAMENTALS OF TRAFFIC NOISE	4
4.0	STATE POLICIES AND PROCEDURES	7
5.0	STUDY METHOD AND PROCEDURES	8
6.0	ANALYSIS AND RESULTS	15
7.0	CONCLUSIONS	18
8.0	REFERENCES	19
APP	PENDIX A - SAMPLE HOMEOWNERS LETTER OF CONSENT	
APP	PENDIX B – MEASUREMENT POSITION PHOTOGRAPHS	
APP	PENDIX C – WEATHER MONITORING DATA	
APP	PENDIX D – NOISE MEASUREMENT DATA AND FIELD MEASUREMENT FORMS	
APP	PENDIX E – INSTRUMENTATION CALIBRATION LOG	

LIST OF TABLES

	PAGE
TABLE I – SUMMARY OF THE MEASURED DATA	IV
TABLE 1 - NOISE MEASUREMENT LOCATIONS	10
TABLE 2 – SUMMARY OF THE MEASURED NOISE LEVELS	16
LIST OF FIGURES	
	PAGE
FIGURE 1 – PROJECT LOCATION MAP	2
FIGURE 2 – PROJECT VICINITY MAP	3
FIGURE 3 – TYPICAL A-WEIGHTED NOISE LEVELS	5
FIGURE 4 – NOISE MEASUREMENT LOCATIONS	12
FIGURE 5 – NOISE MEASUREMENT LOCATIONS	13
FIGURE & MOISE MEASUREMENT LOCATIONS	4.4

EXECUTIVE SUMMARY

A noise measurement study was conducted at 30 residential properties located on Midfield Avenue adjacent to the west side of I-405 between La Tijera Boulevard and Florence Avenue in the Cities of Los Angeles and Inglewood, California. The purpose of the measurements was to determine if the traffic noise levels exceed California Department of Transportation's (Caltrans) "Unusual and Extraordinary Abatement" criteria of 75 dBA at outdoor living space areas. In a previous study conducted by Caltrans, it was determined that the 30 properties would be impacted by future traffic noise which exceeds the Caltrans exterior noise abatement criteria. However, a soundwall would not be effective in abating the traffic noise due to elevations of the properties with respect to the traffic lanes and right-of-way. Therefore, a two phase study is being conducted to determine the following: (1) which of the 30 properties qualify for the unusual and extraordinary abatement; and (2) which of qualifying properties could be benefited by installing acoustical treatments to the homes so that interior traffic noise levels are significantly reduced.

In this first phase of the study, traffic noise levels were monitored continuously on each residential property for several days to determine the maximum hourly average noise level (Leq) created by the I-405 traffic noise. In addition, two High Occupancy Vehicle (HOV) lanes will be fully operational within the next year in this area, and are expected to generate a 2 dB increase in future traffic noise levels. This projected increase was added to the measured level at each residential property to predict the future traffic noise impact with HOV lanes at each property. If the projected future traffic noise level is 75 dBA or higher, the residential building on that property qualifies for building acoustical treatment considerations.

Of the 30 residential properties, 28 homeowners gave permission and allowed access to their property to conduct the traffic noise measurements. The maximum future Leq is over the 75 dBA criteria at the following seven properties: 7518, 7538, 7542, 7558, 7606, 7616, and 7634 Midfield Avenue. Table I shows the maximum future noise levels at all 28 properties, and those which exceed the criteria are shown in bold.

These seven properties would qualify for the building acoustics study for unusual and extraordinary traffic noise abatement. In Phase II, the noise reduction for each of the seven buildings will be measured to determine the maximum hourly Leq on the inside of the homes. The noise reduction tests will measure the composite performance of the existing build construction materials in each of the homes. The noise reduction tests will determine weaknesses in the building shell such as walls, windows and doors, vents, and other noise flanking paths. The second phase of this study will also provide specifications to improve the building shell noise reduction for homes which are found to be above the Caltrans interior noise criteria.

TABLE I - SUMMARY OF THE MEASURED DATA

Address	Max Existing Leq, dBA	Caltrans Measured Leq, dBA	Max Future Leq, dBA
7518 Midfield Ave	75.3	**	77.3
7522 Midfield Ave	71.7	**	73.7
7528 Midfield Ave	71.3 *	**	73.3
7538 Midfield Ave	73.3	72.8	75.3
7542 Midfield Ave	75.2	76.0	78.0
7548 Midfield Ave	72.1	++	74.1
7552 Midfield Ave	69.9	44	71.9
7558 Midfield Ave	74.8	**	76.8
7562 Midfield Ave	70.9	**	72.9
7568 Midfield Ave	75.4 **	70.4 ***	72.4
7572 Midfield Ave	72.5	**	74.5
7578 Midfield Ave	72.6	***	74.6
7600 Midfield Ave	70.6	**	72.6
7606 Midfield Ave	74.3	72.0	76.3
7612 Midfield Ave	72.5	71.6	74.5
7616 Midfield Ave	74.3	**	76.3
7620 Midfield Ave	70.5	**	72.5
7626 Midfield Ave	68.8	**	70.8
7634 Midfield Ave	71.9	76.9	78.9
7700 Midfield Ave	71.6	**	73.6
7706 Midfield Ave	68.3	**	70.3
7710 Midfield Ave	68.2		70.2
7716 Midfield Ave	68.8	**	70.8
7722 Midfield Ave	69.0		71.0
7726 Midfield Ave	72.0	66.9	74.0
7732 Midfield Ave	65.0	***	67.0
7736 Midfield Ave	67.4		69.4
7742 Midfield Ave	64.3	**	66.3

Notes: * The maximum measured Leq at 7528 was 76.3 which was measured with the microphone placed on top of a table near the back yard fence line to protect it from the property owner's dogs. Since the microphone height was above the fence line, the measured levels do not show the effect of the fence attenuation. Therefore, the measured traffic noise level was adjusted downward by 5 dB to include the effect of the fence attenuation. This adjustment is consistent with the measurements conducted at 7568, both with and without fence attenuation.

** The maximum Leq at 7568 represents the traffic noise level at the top of the back yard fence, which was measured at the request of the property owner.

*** The maximum Leq measured by Caltrans was 1.5 meters (5 feet) above ground level, and was below the rear fence line. This position is consistent with Caltrans procedures and all other measurement locations; therefore, the Caltrans measurement was used to project the maximum future level.

Bold values indicate an impact which exceeds criteria.

1.0 INTRODUCTION

This study was conducted to determine which homes among a group of houses located west of I-405 on Midfield Avenue between La Tijera Boulevard and Florence Avenue are qualified for acoustical building improvements in order to abate traffic noise. It was previously determined that a soundwall would not be effective in abating the traffic noise impact for approximately 30 homes in this area. Prior to this study, preliminary measurements were conducted by California Department of Transportation (Caltrans) at a few locations in the study area to determine how high the traffic noise levels currently are. Some were found to be above 75 dBA, which indicated that some homes may qualify for acoustical treatments. Figure 1 shows the project location map. Figure 2 is a vicinity map showing the region of residential properties included in this study, and the approximate locations of the existing soundwalls that were built just to the north and south of the study area.

A second phase of this study involves the analysis, design, and specification of acoustical building treatments. The second phase is anticipated to follow this study based on the conclusions of the traffic noise measurements presented herein.

2.0 PROJECT DESCRIPTION

Caltrans is constructing High Occupancy Vehicle (HOV) lanes on northbound and southbound of I-405 from north of Route 105 Freeway to south of Route 90 Freeway. As part of this project a noise study was conducted and soundwalls were recommended for several locations. Homes located in the study area are between two soundwalls. A soundwall within State right-of-way would not be feasible for these homes due to the depressed nature of the traffic lanes and right-of-way compared to the higher elevation of the residential properties. A soundwall inside the private property was considered but it was determined that it will not be feasible because all the homeowners did not agree with building a soundwall inside their property (Caltrans, 2001). Further more, the backyard fences of these homes are not inline with respect to each other, which makes it difficult to construct an effective continuous soundwall.




FIGURE 1 - PROJECT LOCATION MAP




FIGURE 2 - PROJECT VICINITY MAP

3.0 FUNDAMENTALS OF TRAFFIC NOISE

A brief discussion of fundamental traffic noise concepts is provided in this section.

Sound, Noise, and Acoustics

Sound is a disturbance created by a moving or vibrating source in a gaseous or liquid medium or the elastic stage of a solid and is capable of being detected by the hearing organs. Sound may be thought of as the mechanical energy of a vibrating object transmitted by pressure waves through a medium to a human ear. For traffic sound, the medium of concern is air. *Noise* is defined as sound that is loud, unpleasant, unexpected, or undesired.

Frequency and Hertz

A continuous sound can be described by its *frequency* (pitch) and its *amplitude* (loudness). Frequency relates to the number of pressure oscillations per second. Low-frequency sounds are low in pitch, like the low notes on a piano, whereas high-frequency sounds are high in pitch, like the high notes on a piano. Frequency is expressed in terms of oscillations, or cycles, per second. Cycles per second are commonly referred to as Hertz (Hz). The extreme range of frequencies that can be heard by the healthiest human ears spans from 16–20 Hz on the low end to about 20,000 Hz (or 20 kHz) on the high end.

Sound Pressure Levels and Decibels

The *amplitude* of a sound determines its loudness. Loudness of sound increases and decreases with increasing and decreasing amplitude. Sound pressure amplitude is measured in units of micro-Newton per square meter (N/m^2) , also called micro-Pascal (μPa) . One μPa is approximately one hundred billionths (0.00000000001) of normal atmospheric pressure. Sound pressure level (Lp) is used to describe in logarithmic units the ratio of actual sound pressures to a reference pressure squared. These units are called decibels, abbreviated dB.

Addition of Decibels

Because decibels are logarithmic units, sound pressure levels cannot be added or subtracted by ordinary arithmetic means. When two sounds of equal L_p are combined, they will produce a combined L_p, which is 3 dB greater than the original individual L_p. In other words, sound energy must be doubled to produce a 3-dB increase. If two sound levels differ by 10 dB or more, the combined L_p is equal to the higher L_p; in other words, the lower sound level does not increase the higher sound level.

A-Weighted Decibels

Sound pressure level alone is not a reliable indicator of loudness. The frequency, or pitch, of a sound also has a substantial effect on how humans will respond. Although the intensity (energy per unit area) of the sound is a purely physical quantity, the loudness or human response is determined by the characteristics of the human ear. In general, the healthy human ear is most sensitive to sounds between 1,000 Hz and 5,000 Hz, and it perceives a sound within that range as being more intense than a sound of higher or lower frequency with the same magnitude. A series of Lp adjustments is usually applied to the sound level at different frequencies to approximate the frequency response of the human ear. These adjustments are referred to as a weighting network. The A-scale weighting network approximates the frequency response of the average young ear when listening to most ordinary sounds. Noise levels for traffic noise reports are typically reported in terms of A-weighted decibels (dBA). In environmental noise studies, A-weighted Lps are commonly referred to as noise levels. Figure 3 shows typical A-weighted noise levels.

Human Response to Changes in Noise Levels

It is widely accepted that the average healthy ear can barely perceive noise level changes of 3 dB. A change of 5 dB is readily perceptible, and a change of 10 dB is perceived as being twice or half as loud. As discussed previously, a doubling of sound energy results in a 3 dB increase in sound, which means that a doubling of sound energy (e.g., doubling the volume of traffic on a highway) would result in a barely perceptible change in sound level.

Noise Descriptors

Noise in our daily environment fluctuates over time. Some noise levels occur in regular patterns. others are random. Some noise levels fluctuate rapidly, others Some noise levels vary slowly. widely. others are relatively constant. Various noise descriptors have been developed to describe time-varying noise levels. following is a list of the noise descriptors most commonly used in traffic noise analysis:




FIGURE 3 – TYPICAL A-WEIGHTED NOISE LEVELS

- ❖ Equivalent Sound Level (Leq(h)) Leq(h) represents an average of the sound energy occurring over a specified period. Leq(h) is, in effect, the steady-state sound level that, in a stated period, would contain the same acoustical energy as the time-varying sound that actually occurs during the same period. The 1-hour A-weighted equivalent sound level, Leq(h), is the energy average of the A-weighted sound levels occurring during a 1-hour period and is the basis for Noise Abatement Criteria (NAC) used by Caltrans and the FHWA.
- ❖ Maximum Sound Level (Lmax) Lmax is the highest instantaneous sound level measured during a specified period.
- ❖ Insertion Loss (I.L.) I.L. is the actual noise level reduction at a specific receiver due to construction a noise barrier between the noise source (traffic) and the receiver. Generally, it is the net effect of the soundwall attenuation and the loss due to ground effects.

Sound Propagation

When sound propagates over a distance, it changes in both level and frequency content. The manner in which noise reduces with distance depends on the following factors:

- ❖ Geometric spreading Sound from a small, localized source (i.e., a point source) radiates uniformly outward as it travels away from the source in a spherical pattern. The sound level attenuates (or drops off) at a rate of 6 dB for each doubling of distance. Highway noise is not a single, stationary point source of sound. The movement of the vehicles on a highway makes the source of the sound appear to emanate from a line (i.e., a line source) rather than a point. This line source results in cylindrical spreading rather than the spherical spreading that results from a point source. The change in sound level from a line source is 3 dB per doubling of distance.
- Ground absorption Most often, the noise path between the highway and the observer is very close to the ground. Noise attenuation from ground absorption and reflective wave canceling adds to the attenuation associated with geometric spreading. Traditionally, the excess attenuation has also been expressed in terms of attenuation per doubling of distance. For acoustically hard sites (i.e., those sites with a reflective surface, such as a parking lot or a smooth body of water, between the source and the receiver), no excess ground attenuation is assumed. For acoustically absorptive or soft sites (i.e., those sites with an absorptive ground surface, such as soft dirt, grass, or scattered bushes and trees, between the source and the receiver), an excess ground attenuation value of 1.5 dB per doubling of distance is normally assumed. When added to the geometric spreading, the excess ground attenuation results in an overall drop-off rate of 4.5 dB per doubling of distance for a line source and 7.5 dB per doubling of distance for a point source.
- Atmospheric effects Research by Caltrans and others has shown that atmospheric conditions can have a significant effect on noise levels when noise receptors are located more than 60 meters (200 feet) from a highway. Wind has been shown to be the most important meteorological factor within approximately 150 meters (500 feet) of the source, whereas vertical air temperature gradients are more important for greater distances. Other factors such as air temperature, humidity, and turbulence also have significant effects.

Building Acoustics

Under conditions of extraordinary traffic noise impact, noise abatement strategies such as improved building insulation can be considered to reduce the exterior noise level at the interior of building structures. Improvement in a building's sound insulation can be achieved by using items such as: sound-rated windows and doors, additional glass fiber or similar insulating material for walls and attic spaces, perimeter caulking at adjoining building elements, an airconditioning system so that windows may remain closed during hot weather, and treatments to exterior vents to prevent noise from entering the building through the vent or duct. Typical residential building construction generally provides 10 to 15 dB of noise reduction from the exterior to the interior when windows are open for ventilation, and 18 to 23 dB of reduction with closed windows. When acoustical treatments such as those mentioned above are applied to a residential building, the noise reduction performance can range from 25 to 35 dB, an increase of 7 to 12 dB compared to a non-treated building with windows closed.

4.0 STATE POLICIES AND PROCEDURES

The Caltrans noise abatement design goals include provisions for applying acoustical building treatments to impacted residences in order to abate traffic noise at the interior of the home. Although rarely employed, this measure is considered when conventional types of abatement such as soundwalls are found to be ineffective. This type of noise abatement falls into a special category called, "Unusual and Extraordinary Abatement." The following is taken from the Caltrans Traffic Noise Analysis Protocol document (Caltrans, 1998a):

Noise insulation will not normally be provided in private residential dwellings, and may be provided only when severe traffic noise impacts are anticipated and normal abatement measures are physically not feasible or are economically unreasonable. When considering extraordinary abatement measures, it must be demonstrated that the affected activities experience traffic noise impacts to a far greater degree than other similar activities adjacent to highway facilities; i.e., private residential dwelling units will have after-project exterior noise levels of 75 dBA, Leq(h), or more..."

Therefore, the noise limit criteria used in this study will be a peak noise hour Leq of 75 dBA. Any home where the projected future traffic noise level with the proposed HOV lanes is found to be equal to or above the 75 dBA limit qualifies for further consideration of acoustical building treatments. Acoustical building treatments are applied to the home to improve the noise insulation from the exterior to the interior of the home. Acoustical treatments may consist of one or more of the following: replacement of existing windows and doors with sound-rated products; caulking applications; treatments to exterior penetrations such as vents; the addition of insulation materials; and the installation of air-conditioning systems for the purpose of allowing the homeowner to keep windows and doors closed for traffic noise abatement. The following statement is also taken from the Caltrans protocol:

"When noise abatement is provided for public or private properties in line with this policy, an agreement must be entered into with the owner of the subject property which specifies that Caltrans is not responsible for any future costs of operating and/or maintaining the noise abatement improvements; i.e., air conditioning, caulking, etc."

5.0 STUDY METHOD AND PROCEDURES

Thirty homes were originally selected for this study in the 7500, 7600, and 7700 blocks of Midfield Avenue based on prior studies that determined which properties could not be abated effectively with soundwalls. A letter was sent from Caltrans to thirty homeowners requesting their participation in the acoustical study, and their consent to access their property. A blank sample of the signed letter is included in Appendix A. The homeowners were contacted by phone the week before the measurements to arrange for access to their property. While contacting the homeowners by phone to schedule access to the property, noise measurement systems were confirmed for installation at 28 homes. Of the remaining two, one homeowner (7746) withdrew their agreement to participate stating that the measurements would impose an inconvenience and, they had already installed acoustical building treatments similar to those that would be considered in this project. The second homeowner (7532) indicated that their pet would likely disturb and possibly damage the measurement equipment if left unattended in the backyard. The homeowner was unwilling to restrain or isolate the pet throughout the duration of the measurements to insure this would not happen. No measurements were conducted at those two properties.

Originally, 28 noise measurement systems were configured to measure the hourly Leq continuously at each location. All systems were also set to record hourly statistics including the minimums, maximums, and exceedance percentiles. This data was stored internally in the measurement systems so that it could be downloaded at the end of the measurements. Weather conditions were noted during the initial set-up of the instrumentation. The temperature and relative humidity were monitored and recorded continuously throughout the week at one of the measurement sites. Wind speed and direction were measured and recorded during the first twelve hours of the tests at the same site. Additional wind data was collected from a weather data service for the Santa Monica area (Weather, 2005). Figures 4 through 6 provide a layout plan showing the measurement locations.

The noise measurements began on Monday, January 24, 2005 and continue throughout the week. One of the measurement systems failed during this measurement week; therefore, it had to be repeated at a later date. The following is a list of the equipment that was used for this study:

Sound Level Meter Systems:

- 17 Larson Davis model 870A sound level meters with model 900B microphone preamplifiers having an American National Standards Institute (ANSI) Type 1 accuracy rating. (One of these systems was used during the week of January 24th, and a second time during the week of February 28th, when one of the measurements had to be repeated.)
- 5 Rion model NL-31 sound level meters and preamplifiers having an ANSI Type 1 accuracy rating.
- 3 Larson Davis model 2900 sound level meters with model 900B microphone preamplifiers having an ANSI Type 1 accuracy rating.
- 1 Larson Davis model 820 sound level meter with a model 828 microphone preamplifier having an ANSI Type 1 accuracy rating.
- 1 Larson Davis model 812 sound level meter with a model 828 microphone preamplifier having an ANSI Type 1 accuracy rating.
- 27 1/2-inch, random-incidence, voltage-polarized or pre-polarized condenser microphones as recommended by the manufactures for suitable use with the above sound level metering systems certified to meet an ANSI Type 1 accuracy rating.

Weather Systems:

- Kestrel 3000 Pocket Weather Meter for temperature and relative humidity checks.
- Davis Instruments meteorological monitoring system model Weather Wizard III attached to a portable computer for the collection and storing of continuous temperature, wind, and humidity data.
- Onset Computer Corporation HOBO, Pro Series, model H08-032-08 humidity sensor and data logger, with solar radiation shield.

Other Instrumentation:

- Microphone cables and tripod mounts for the microphones.
- 2 Larson Davis model CA250 and 1 Bruel & Kjaer type 4230 acoustical field calibrators.
- Microphone wind screens: 4-inch and 6-inch diameter for pre-polarized microphones, and outdoor environmental protection systems for non-polarized microphones.
- External batteries and A/C power adapters as required for powering the sound level meter systems.
- Larson Davis model 2510 1.44 MB external floppy drive accessory for LD2900 sound level meter data retrieval.

Selection of the microphone measurement position are base on the following requirements:

- Common outdoor human use area.
- Acoustically representative and equivalent of the area of concern.
- Locations expected to receive the highest noise impacts.

Noise measurements were conducted in conformance with Caltrans' Technical Noise Supplement (Caltrans, 1998b). The followings are the brief descriptions of measurement procedures:

- Most of the microphones for sound level meters were placed 1.5 meters (5 feet) above the ground, deck, or patio areas for the noise measurements. Exceptions to this are described below.
- Sound level meters were calibrated before and after each measurement. Any differences in the calibration were noted.
- Following calibration of equipment a wind screen was placed over the microphone.
- Frequency weighting was set on "A" and slow response.

Table 1 provides a list of the measurement addresses, equipment types, microphone positions, and property line wall information. Installations on decks or raised patios resulted in a microphone height which was higher than 1.5 meters (5 feet) above the surrounding ground and yard areas. Many of the homes contained wooden or masonry fences parallel to I-405, which crossed through the back of the property, at a point where the terrain began slopping down toward the highway. At one location (7568), the owner stated that the wooden fence located at the back of the rear yard would be removed, and requested that the measurement be conducted so that the fence does not influence the traffic noise. Therefore, the microphone was placed approximately 0.6 meters (2 feet) above the top of the fence at the owner's request. At another location (7528), the microphone was placed on top of a 0.9 meter (3 feet) high table near the rear fence line to prevent the owners dogs from tipping the tripod over during the measurements. This also produced a microphone height which was above the rear fence line. Appendix B contains photographs of each noise measurement position.

The weather monitoring station was installed at 7606 Midfield Avenue which is located approximately midway between the 28 measurement positions. The weather station was set to record wind speed and direction, temperature, and relative humidity. The location of the weather monitoring station is shown on Figure 4, with photographs of it shown in Appendix B.

TABLE 1 – NOISE MEASUREMENT LOCATIONS

Midfield Avenue Address	Equip Typ e	Microphone Position	North Property Line Wall Hgt, meters (feet) & Type	East Property Line Wall Hgt, meters (feet) & Type	South Property Line Wall Hgt, meters (feet) & Type
7518	LD 870	17.7 m (58 ft) from back of house, 1.5 m (5 ft) above ground	none	none	none
7522	Rion NL31	10.2 m (33.5 ft) from back of house, 1.5 m (5 ft) above ground	1.7 (5.5) masonry	1.2 (4) masonry	1.4 (4.7) masonry
7528	LD 870	0.9 m (3 ft) from E. fence line on top of table, 1.5 m (5 ft) above table top *	1.5 (5) masonry	1.8 (6) wood	garage
7532		Not Installed because of dogs.			
7538	LD 870	12.8 m (42 ft) from back of house, 1.5 m (5 ft) above ground	2.1 (7) wood	none	1.4 (4.5) wood
7542	Rion NL31	4.4 m (14.5 ft) from back of house, 1.5 m (5 ft) above conc deck area	none	none	1.8 (6) wood
7548	LD 870	9.3 m (30.5 ft) from back of house, 1.5 m (5 ft) above ground	1.8 (6) wood	none	2.1 (7) masonry
7552	LD 870	even with back of house on raised patio 1.5 m (5 ft) above raised patio	1.5 (5) masonry	2.1 (7) wood	garage
7558	LD 870	6.7 m (22 ft) from back of house, 1.5 m (5 ft) above ground	garage	none	greenhouse
7562	LD 870	2.7 m (9 ft) from back of house on deck, 1.5 m (5 ft) above deck	2.4 (8) masonry, wood	2.4 (8) wood	1.9 (6.3) masonry
7568	LD 870	8.5 m (28 ft) from back of house on rear fence, 2.1 m (7 ft) above ground **	1.7 (5.5) masonry	1.5 (fi) wood	1.5 (5) masonry
7572	Rion NL31	3.5 m (11.5 ft) from back of house on deck, 2.3 m (7.7 ft) above ground	1.5 (5) masonry	1.8 (6) wood & sheds	3.0 (10) wood fence above masonry wall
7578	LD 870	3.0 m (10 ft) from back of house on deck, 1.5 m (5 ft) above the deck	1.8 (6) masonry	1.8 (6) wood	1.8 (6) masonry
7600	LD 2900	4.6 m (15 ft) from back of house, 2.1 m (7 ft) above ground attached to post to protect from owner's dog	1.4 (4.5) masonry	2.6 (8.5) wood	1.8 (6) wood

Notes: * The measured noise levels at 7528 represents the traffic noise level near the back yard fence on top of a table in order to keep the equipment out of reach of the owner's dogs.

** The measured noise levels at 7568 represents the traffic noise level at the top of the back yard fence, which was measured at the request of the property owner.

TABLE 1 (CONT'D) - NOISE MEASUREMENT LOCATIONS

Midfield Avenue Address	Equip Type	Microphone Position	North P.L. Wall Hgt, meters (feet) & Type	East P.L. Wall Hgt, meters (feet) & Type	South P.L. Wall Hgt, meters (feet) & Type
7606	LD 870 & weather sta.	3 m (10 ft) from back of house on patio deck, 1.5 m (5 ft) above deck	1.8 (6) wood	1.7 (5.5) wood	none
7612	Rion NL31	11.6 m (38 ft) from back of house, 1.5 m (5 ft) above ground	none	none	1.7 (5.5) wood
7616	LD 870	2.1 m (7 ft) from back of house, 1.5 m (5 ft) above ground	1.2 (4) wood	none	1.8 (6) wood
7620	Rion NL31	5.8 m (19 ft) from back of house, 1.5 m (5 ft) above ground	1.8 (6) wood	1.8 (6) wood	1.8 (6) wood
7626	LD 870	4.6 m (15 ft) from back of house, 1.5 m (5 ft) above ground	1.7 (5.5) wood	1.7 (5.5) wood	1.7 (5.5) wood & garage
7634	LD 820	4.6 m (15 ft) from back of house, 1.5 m (5 ft) above ground	none	none	none
7700	LD 870	8.8 m (29 ft) from back of house, 1.5 m (5 ft) above ground	1.8 (6) wood	none	1.8 (6) wood
7706	LD 2900	4.0 m (13 ft) from back of house, 1.5 m (5 ft) above ground	1.8 (6) wood	1.8 (6) wood	1.8 (6) wood
7710	LD 870	4.6 m (15 ft) from back of house, 1.5 m (5 ft) above ground	1.8 (6) masonry & wood	2.7 (9) wood	1.8 (6) masonry & wood
7716	LD 870	4.9 m (16 ft) from back of house, 1.5 m (5 ft) above ground	1.8 (6) masonry & wood	1.2 (4) wood	2.3 (7.5) wood
7722	LD 870	5.5 m (18 ft) from back of house, 1.5 m (5 ft) above ground	1.8 (6) wood	none	1.8 (6) wood
7726	LD 870	3.7 m (12 ft) from back of house on patio, 1.5 m (5 ft) above ground	2.4 (8) wood	2.4 (8) wood	2.4 (8) wood
7732	LD 870 7.3 m (24 ft) from back of house, 1.5 m (5 ft) above ground		2 (6.5) masonry	2 (6.5) masonry & shed	1.8 (6) masonry
7736	LD 2900	11.9 m (39 ft) from back of house, 1.5 m (5 ft) above ground	1.8 (6) masonry	none	1.8 (6) masonry
7742	LD 812	4.6 m (15 ft) from back of house, 1.5 m (5 ft) above ground	1.5 (5) masonry	2.4 (8) masonry	1.5 (5) masonry
7746		Owner decided not to participate in study.			

6.0 ANALYSIS AND RESULTS

6.1 WEATHER CONDITIONS

Skies ranged from hazy sun to mostly cloudy on Monday and Tuesday, January 24th and 25th, 2005. Weather reports forecasted rain for Wednesday, and therefore all microphones were covered with a plastic bag between 7:00 and 9:00 p.m. on Tuesday evening. Rain and wet periods occurred during the following periods:

- Tuesday evening (1-25-05) starting at 8 p.m. through 8 a.m. Wednesday morning.
- Friday morning (1-27-05) starting at 8 a.m. off and on until midnight Friday night.

The microphones were uncovered between Wednesday evening at 6:00 p.m. and Thursday morning at 11:00 a.m. However, the microphone systems were not covered on Friday. The weekend weather was partly cloudy to mostly sunny. All data during rainy periods are unreported since rain causes an inaccurate measurement of the traffic noise. Although temperature and humidity measurements continued throughout the duration of the noise measurements, the wind data logger experienced a problem and stopped recording data after approximately 12 hours of recording. During that time, wind conditions were mostly calm and the average wind speed never rose above 6.4 km/h (4 mph). Generalized wind data for the Santa Monica area was also obtained and tabulated (Weather, 2005). The weather monitoring data is shown in Appendix C.

6.2 NOISE MEASUREMENT DATA

All but three of the 28 measurement systems were functional and collecting data by 4 p.m. Monday evening, January 24, 2005. The measurement system at 7732 became operational at 5:00 p.m. The system at 7528 became operational at 6:00 pm. The third system at 7562, malfunctioned and did not collect any data during that week. However, the measurement was repeated at 7562 during the week of February 28 through March 4, 2005. There were no roadway construction activities occurring during either of these measurement weeks.

After a final field calibration, the measurement systems were retrieved from the residential properties. The data was downloaded from all instruments, and the before and after calibration records were compared to determine calibration drift. The calibration drift was between 0.0 and 0.4 dB at all 28 measurement sites. No adjustments were made for calibration drift.

The hourly Leq noise levels were plotted and reviewed to see if any anomalies were causing the hourly patterns to be unusually high. If an unusual pattern was found, the statistical levels and history data for those periods were reviewed to determine if the data suggested any noise characteristics that are inconsistent with typical traffic noise. Comparisons were also made at adjacent measurement sites to determine if the noise was local to the microphone. If a high noise level affected only one site but not adjacent sites, this suggests a non-traffic related noise. If a high noise level appeared at two or three adjacent sites, this suggests either an unusually loud motor vehicle or an aircraft overflight. If data was found that is inconsistent with known traffic noise characteristics, the measured level was flagged as "non-traffic related noise" on the measurement graphs. A summary of the measured levels are provided in Table 2. The measurement graphs, Leq data, and field measurement notes for all 28 measurement locations are provided in Appendix D.

Table 2 shows the highest hourly Leq that was measured for each day of the week, and the highest level for the entire week of measurement, shown as "Max Existing Leq." The Caltrans measurements conducted in April and May of 2004 are also provided in Table 2. The future noise level was projected to include the traffic noise increase due to the new HOV lanes (currently under construction) by adding 2 dB to the highest measured level (Caltrans, 2001).

TABLE 2 – SUMMARY OF THE MEASURED NOISE LEVELS

			Highest Recor	Highest Recorded Hourly Leg Per Day, dBA	Per Day, dBA			Max	Caltrans	Max
Address	Monday	Tuesday	Thursday	Friday	Saturday	Sunday	Monday	Existing	Measured	Future
	1/24/2005	1/25/2005	1/27/2005	1/28/2005	1/29/2005	1/30/2005	1/31/2005	Leg, dBA	Leq, dBA	Leq, dBA
7518 Midfeld Ave	74.9	75.3			:	;		75.3	:	77.3
9	70.5	71.3	71.1	71.7	71.5	71.3		71.7	•	73.7
4.2	74.1	74.7	76.3	75.3	74.6	75.3	75.2	71.3 *	•	73.3
7538 Andreid Ave	70.8	71.7	72.5	72.9	72.8	73.3	73.3	73.3	72.8	75.3
7542 Mildfald Ave	74.2	74.8	75.2	75.0	74.7	75.0		75.2	76.0	78.0
7548 Midfield Ave	70.5	71.5	71.6	71.6	71.8	72.1	71.8	72.1	:	74.1
7552 Midfield Ave	62.9	67.2	67.0	67.4	6.69	68.3	68.2	6.69	;	71.9
7558 Midfield Ave	73.8	74.5	74.4	74.8	73.9	74.5	74.8	74.8	;	76.8
7568 Midfield Ave	74.5	75.0	75.4	75.0	75.2	73.6	-	75.4 **	70.4 ***	72.4
7572 Marie d Ave	70.1	71.0	70.8	71.5	72.5	71.2		72.5	;	74.5
7578 Midfield Ave	70.6	71.5	71.3	71.9	72.6	72.1	72.1	72.6	:	74.6
7600 Midfield Ave	69.6	70.2	70.0	70.6	70.6	70.4	70.2	70.6	:	72.6
7606 Mildfeld Ave	72.9	73.5	73.6	73.9	74.3	74.1	74.0	74.3	72.0	76.3
7612 Midfield Ave	71.3	72.2	72.0	72.3	72.5	72.0		72.5	71.6	74.5
7616 Midfield Ave	73.4	74.0	74.3	74.0	74.1	74.1	74.1	74.3	:	76.3
7620 Midfield Ave	67.3	68.1	68.4	68.2	70.5	69.0	•	70.5	;	72.5
7626 Mid™id Ave	65.4	66.2	66.4	65.3	68.8	67.6	67.1	68.8	:	70.8
7634 Midfeld Ave	71.1	71.6	71.5	71.8	70.4	71.1	71.9	71.9	6.92	78.9
7700 Midfield Ave	70.1	71.6	70.5	71.1	6.69	70.8	71.0	71.6	;	73.6
7706 Midfield Ave	66.1	67.3	9.79	68.3	68.0	67.1	;	68.3	:	70.3
7710 Midesid Ave	66.3	9.99	2'99	66.7	68.2	66.7	67.1	68.2	;	70.2
7716 Midipid Ave	67.8	68.3	68.1	9.89	68.8	68.4	68.5	68.8	•	70.8
7722 Midial Ave	68.0	68.3	68.6	68.8	68.7	69.0	68.9	69.0	:	71.0
7726 Mideliald Ave	64.2	66.2	65.5	66.2	66.1	72.0	65.6	72.0	6.99	74.0
7732 Midial Ave	62.3	62.8	63.2	64.6	65.0	64.2	63.9	65.0	:	67.0
7736 Midial Ave	65.5	65.8	67.4	0.99	0.99	67.4	67.0	67.4	:	69.4
7742 Marield Ave	61.8	61.6	62.7	61.7	64.3	63.8	63.6	64.3	:	66.3
	Monday	Tuesday	Wednesday	Thursday	Friday	Saturday	Sunday			
	2/28/2005	3/1/2005	3/2/2005	3/3/2005	3/4/2005	3/2/600	3/0/2003	Į,		6
7562 Marield Ave	69.3	70.7	70.9	69.4	2.69	•	:	6.07	:	72.9

it from the property owner's dogs. Since the microphone height was above the fence line, the measured levels do not show the effect of the fence attenuation. Therefore, the measured traffic noise level was adjusted downward by 5 dB to include the effect of the fence attenuation. This adjustment is The maximum measured Leq at 7528 was 76.3 which was measured with the microphone placed on top of a table near the back yard fence line to protect consistent with the measurements conducted at 7568, both with and without fence attenuation. Notes:

The maximum Let at 7568 represents the traffic noise level at the top of the back yard fence, which was measured at the request of the property owner. *

The maximum Leq measured by Caltrans was 1.5 meters (5 feet) above ground level, and was below the rear fence line. This position is consistent with Caltrans procedures and all other measurement locations, and was therefore used to project the maximum future level.

Bold values indicate an impact which exceeds criteria.

At some locations, the Caltrans measured data is higher than the measured data in this study. The higher of the two was used as the basis for projecting the future noise level. Table 2 shows future projection as the "Max Future Leq."

The maximum Leq's at 7568 Midfield were measured with the microphone placed at the top of the rear fence line at the request of the property owner who stated that the fence would be removed. However, Caltrans does not consider the traffic noise level at the top of a property line fence to be representative of the impact to the outdoor use area. Therefore, the Caltrans measurement result shown in Table 2 substituted at this location since the maximum Leq measured by Caltrans was 1.5 meters (5 feet) above ground level, and is consistent with other measurement positions. This position is consistent with Caltrans procedures and all other measurement locations, and was therefore used to project the maximum future level at that location.

In Table 1, the maximum measured Leq at 7528 was 76.3 on Thursday, the 27th of January. The traffic noise levels at this location were measured with the microphone placed on top of a table near the back yard fence line to protect it from the property owner's dogs. Since the microphone height was above the fence line, the measured levels do not show the effect of the fence attenuation. Therefore, the measured traffic noise level was adjusted downward by 5 dB to include the effect of the fence attenuation, estimated at 71.3. This adjustment is consistent with the measurements conducted at 7568, both with and without fence attenuation.

The Centinela Adobe home property located at 7634 Midfield Avenue is owned by the City of Inglewood, and has a total of three structures. Per the Caltrans Environmental Division, the Adobe home has been listed with the National Historic Registry since 1974. There are very stringent restrictions on this dwelling, especially for upgrading or acoustical treatments. Windows are not allowed to be replaced and other types of abatement such as sealing is limited. If noise reduction treatments are to be done at this location, Caltrans will need to confer and comply with the National Registry guidelines, and insure that the modifications are in strict conformance. In addition, the acoustical treatments cost should be estimated substantially higher than other locations due the stringent requirements for historic structures. There is also a second structure on the same property which is anticipated to also be on the historic registry as a museum home. The same guidelines would apply for it as well. The third structure on the property, which is a museum was constructed about 20 years ago and is not listed in the registry.

7.0 CONCLUSIONS

Of the 28 measurement locations, the maximum future Leq is over the 75 dBA criteria at the following seven properties: 7518, 7538, 7542, 7558, 7606, 7616, and 7634 Midfield Avenue. The maximum future noise levels in Table 2 which exceed the criteria are shown in bold.

These seven properties would qualify for Phase II of the building acoustics study for traffic noise abatement. In Phase II, the noise reduction for each of the seven buildings will be measured to determine the maximum hourly Leq on the inside of the homes. The noise reduction tests will measure the composite performance of the existing build construction materials in each of the homes.

8.0 REFERENCES

- Caltrans, 1998a. California Department of Transportation. <u>Traffic Noise Analysis Protocol for New Highway Construction and Reconstruction Projects</u>, October.
- Caltrans, 1998b. California Department of Transportation. <u>Technical Noise Supplement to the Traffic Noise Analysis Protocol</u>, October.
- Caltrans, 2001. Noise Study Report, Route 405 Freeway, from north of Route 105 Freeway to south of Route 90 Freeway, prepared by California Department of Transportation, January.
- Weather, 2005. The Weather Channel internet site, www.weather.com weather report data for Santa Monica, California; data was collected for dates January 24 through January 31, and March 1 through March 3.

APPENDIX A

Sample Homeowners Letter of Consent

STATE OF CALIFORNIA - BUSINESS, TRANSPORTATION AND HOUSING AGENCY

ARNOLD SCHWARZENEGGER, GOVERNOY

CEPARTMENT OF TRANSPORTATION

SOUTHERN RIGHT OF WAY REGION

100 South MAIN Street Los Angeles, CA 90012 Phone: (213) 897-1901 Fex: (213) 897-1962

District 07 R/W Field Office



December 7 2004

07-LA-405 EA: 1198U3 APN:

Dear Property Owner:

The California Department of Transportation (Caltrans) will be conducting the first phase of a noise abatement study for 30 homes located along Midfield Avenue in Los Angeles. The second phase will only include the properties where the noise level as indicated by the noise study results is 75 decibels or more. The Department of Transportation has installed soundwalls to abate the noise from interstate 405 Freeway between La Tierja and Florence Boulevard in Los Angeles. The soundwalls are not effective in abating noise impacts on approximately 30 houses that are located at higher elevations than the Freeway. The purpose of this letter is to notify you that the noise study or test originally planued for December has been rescheduled for the month of January. Therefore another permit needs to be signed by every property owner.

The Environmental Engineering Branch will need a Permit to Enter from each owner in order to access the property to conduct the noise study of tests. The consultant hired to perform the tests will require access to the property from annuary 10, 2005 through January 10. The consultant will need to install the equipment, and once the 72-hour moise accurate study is completed some equipment from your property. Please note if there is rainfull the noise study will be cancelled and rescheduled to a later date.

A microphone will be securely mounted on a five-foot high tripod, and a noise level meter will be placed in the rear yard. The items will be placed in the rear of the property within the study limits. Photographs will be taken of the subject property and the studies will be completed by October of 2005. The noise measuring devises and equipment must not be tampered with once they are placed on the property.

The Department would like to complete the first phase of the noise abatement study as soon as possible. Therefore indicate in the space provided on the following page the best date and time to contact you, provide your phone number, and list any special conditions regarding your property that the consultant needs to know in order to perform the study.

Please return the signed permit to this office by December 22 2004, a self-addressed envelope has been enclosed for your convenience. (a copy is enclosed for your records) The consultants employed by Parsons Engineering Company, and he will contact you regarding the date and time to install the equipment.

Sincerely yours


Right of Way Agent

Parcel: APN NO.	Page 2 of 2
	California, Department of Transportation to enter upon the property y of Los Angeles to conduct the noise abatement study.
	oility caused by or in connection with the performance of the noise at of Transportation and /or its representatives.
The State shall defend, indemnify, and he Caused by the State's operations.	old the owner's or their agent, harmless from any liability
Thank you for your cooperation in this matter.	Should you have any questions regarding this request, please contact me a
ACKNOWLEDGEMENT OF RECEIPT OF	THIS LETTER AND CONSENT TO ENTER THE PROPERTY
	APPROVED BY:
Owner's signature	STATE OF CALIFORNIA
	Department of Transportation
	Deborah C. Meyers
Date	Branch Chief R/W Acquisition
Telephone number	

Date

APPENDIX B

Measurement Position Photographs



7518 Midfield Avenue



7522 Midfield Avenue



7528 Midfield Avenue



7538 Midfield Avenue



7542 Midfield Avenue



7548 Midfield Avenue



7552 Midfield Avenue



7558 Midfield Avenue



7562 Midfield Avenue



7568 Midfield Avenue



7572 Midfield Avenue



7578 Midfield Avenue



7600 Midfield Avenue



7606 Midfield Avenue



7612 Midfield Avenue



7616 Midfield Avenue



7620 Midfield Avenue



7626 Midfield Avenue



7634 Midfield Avenue



7700 Midfield Avenue



7706 Midfield Avenue



7710 Midfield Avenue



7716 Midfield Avenue



7722 Midfield Avenue



7726 Midfield Avenue



7732 Midfield Avenue



7736 Midfield Avenue



7736 Midfield Avenue



7742 Midfield Avenue




Weather Station at 7606 Midfield Avenue



Weather Station at 7606 Midfield Avenue

APPENDIX C

Weather Monitoring Data



Temperature and Relative Humidity Data Measured at 7606 Midfield Avenue from January 24 through February 1, 2005

Wind Data for Santa Monica Area

Date	Time	Speed, mph	nd Data Direction
Mon-24-Jan	12:00	Speed, mpn	SW, WSW
MOR1-24-3201	13:00	Calm, 3-8	WSW, SSE
	14:00	6	SW
	15:00	8	SW
	16:00	Calm, 7	SW
	17:00	Calm	OVV
	18:00	3	ENE
	19:00	Calm	
		5	SW
	20:00		
	21:00	Calm	
	22:00	Calm	90
F OF 1	23:00	Calm	
Tue-25-Jan	0;00	Calm	+++
	1:00	3	NE
	2:00	5	NNE
	3:00	3	NNE
	4:00	5.	NNE
	5:00	3	NE
	6:00	3	E
	7:00	Calm	
	8:00	Calm, 6	ENE
	9:00	5	E
	10:00	Calm	
	11:00	5	S
	12:00	8	SSW
	13:00	6	WSW
	14:00	5	Variable
	15:00	6	SW
	16:00	5	Variable
	17:00	6	SW
	18:00	Calm	
	19:00	Calm	
	20:00		
	Committee Commit	Calm 7	WSW
	21:00		
	22:00	3-5	WSW, Variable
North Printers	23:00	Calm	
Wed-26-Jan	0:00	Calm	
	1:00	Calm	
	2:00	Calm	
	3:00	Calm	-
	4:00	Calm	
	5:00	Calm	16-7-11-
	6:00	Calm, 3	Variable
	7:00	Calm	
	8:00	3	SW
	9:00	Calm, 3	Variable
	10:00	3-7	SSW, SW, Variab
	11:00	10	SW
	12:00	5	Variable
	13:00	B	SW
	14:00	9-10	SW
	15:00	9	WSW
	16:00	9	SSW
	17:00	3-8	SW
	18:00	6	SW
	19:00	6-7	SW
	20:00	5-9	SW, WSW
	21:00	6	SW
	22:00	8	WSW
	23:00	Calm	713071

Wind Data for Santa Monica Area (Cont'd)

Date	Time		1 Data
late lat-29-Jan	Time	Speed, mph	Direction
ar-29-Jan	12:00	10	Variable W
	13:00	10	W
	14:00	12	
	15:00	15	NNW
	16:00	16	N
	17:00	15	NNW
	18:00	14	NNW
	19:00	14	NNW
	20:00	16	N
	21:00	12	NNW
	22:00	10	NNW
	23:00	7	Variable
iun-30-Jan	0:00	7	NNE
	1:00	Calm	++
	2:00	Calm	**
	3:00	Calm	
	4:00	3	NE
	5:00	3	N
	6:00	6	E
	7:00	Calm	+
	8:00	Calm	++
	9:00	5.0	E
	10:00	Calm	
	11:00	9	SSW
	12:00	8	SSW
	13:00	7	Variable
	14:00	9	SSW
	15:00	6	Variable
	16:00	3	E
	17:00	3	SSW
	18:00	3	NW
	19:00	7	WNW
	20:00	Calm	44
	21:00	7	NE
	22:00	3	NE
	23:00	5	NE
Aon-31-Jan	0:00	6	NE
	1:00	8	NE
	2:00	5	NNW
	3:00	3	NNW
	4:00	Calm	
	5:00	6	Ē
	6:00	5	E
	7:00	5	E
	8:00	5	Variable
	9:00	5	Variable
	10:00	6	SSW
	11:00	9	SSW
	12:00	9	SW
	13:00	10	SSW
	14:00	8	SSW
	15:00	В	SSW
	16:00	5	Variable
	17:00	Calm	
	18:00	3	N
	19:00	Calm	
	20:00	3	NE
	21:00	5	ESE
	22:00	3	N
	23:00	5	N

Wind Data for Santa Monica Area (Cont'd)

Date	Time	Speed, mph	Data Direction
Sat-29-Jan	12:00	Speed, mpn	Variable
un-Sa-Jun	13:00	10	W
	14:00	12	W
	15:00	15	NNW
	16:00	16	N
	17:00	15	NNW
	18:00	14	NNW
	19:00	14	NNW
	20:00	16	N
	21:00	12	NNW
	22:00	10	NNW
	23:00	7	Variable
un-30-Jan	0:00	7	NNE
uir bu ouri	1:00	Calm	
	2:00	Calm	-
	3:00	Calm	
	4:00	3	NE
	5:00	3	N.
	6:00	6	E
	7:00	Calm	
	8:00	Calm	
	9:00	5.0	E
	10:00	Calm	
	11:00	9	SSW
	12:00	8	SSW
	13:00	7	Variable
Mon-31-Jan	14:00	9	SSW
	15:00	6	Variable
	16:00	3	E
	17:00	3	SSW
	18:00	3	NW
	19:00	7	WNW
	20:00	Caim	441444
	21:00	7	NE
	22:00	3	NE
	23:00	5	NE
Ion 94 Ion	0:00	6	NE
non-an-Jan			NE
	1:00	5	NNW
			NNW
	3:00 4:00	3 Calm	NNW
	5:00	6 B	Ē
	6:00	5	E
	7:00	5	E
	8:00	5	Variable
	9:00	5	Variable
	10:00	6	SSW
	11:00	9	SSW
	12:00	9	SW
	13:00	10	SSW
	14:00	8	SSW
	15:00	8	SSW
		5	Variable
	18:00	Calm	variable
	17:00		N
	18:00	3 Colon	N
	19:00	Çaim	NE
	20:00	3 5	
	21:00		ESE
	22:00	3	N
	23:00	5	N

Wind Data for Santa Monica Area (Cont'd)

Date	There		nd Data
	Time	Speed, mph	Direction
Wed-02-Mar	0:00	3	NNW
	1:00	Calm	
	2:00	Calm	
	3:00	3	NW
	4:00	3	N
	5:00	3	NW
	6:00	Calm	
	7:00	3	NE
	8:00	3	Variable, E
	9:00	6	SSE
	10:00	10	SSW
	11:00	9	SW
	12:00	9	SSW
	13:00	9	SW
	14:00	8-9	WSW, SW
	15:00	- 6	Variable
	16:00	5-7	SW, Variable
	17:00	6, Calm	SSW
	18:00	3	S, SSE
	19:00	3, Calm	SSE, E
	20:00	Calm, 5-6	SE, SSE
	21:00	5-8	SSE, SE
	22:00	3-6	SE, ESE, E
	23:00	Calm	- 100 Marie 100
hu-03-Mar	0:00	5, Calm	WSW
	1:00	Calm	-
	2:00	Calm	-
	3:00	Calm	-
	4:00	Calm	
	5:00	Calm	
	6:00	Calm, 3	NNE
	7:00	Calm	HAC
	8:00	3	Variable
	9:00	3-6	ESE, Variable, SE
	10:00	9	SSW SSW
			SSW
	11:00	9	
	12:00	10	SSW
	13:00	7	WSW
	14:00		WSW
	15:00	8	SW
	16:00	8	WSW
	17:00	8	
	18:00	8	WSW
	19:00	3	Variable
	20:00	6	SW
	21:00	3	SW
	22:00	3-5	SSW, S
of the Adam	23:00	Calm	8
n-04-Mar	0:00	3	
	1:00	5-8	SE
	2:00	6, Calm	SE Variable ERE R
	3:00	Calm, 3-6	Variable, ESE, S
	4:00	5-7, Calm	SSE, S
	5:00	8-9	SSE, SE
	6:00	5-8	SE, ESE
	7:00	5-7	ESE, E
	8:00	3-7	SW, ESE, Variable
	9:00	7	8
	10:00	5	Variable
	11:00	7-9	SSW, Variable, S
	12:00	8	SW

APPENDIX D

Noise Measurement Data

and Field Measurement Forms

75.3 dBA

Hourly Noise Levels, Leq(h)

7518 Midfield Avenue, Inglewood, CA Rear Yard Location:

Position:


1-405 Highway Traffic Sources:

Date:

See attached Noise Measurement Form Notes:

Rain occurred all day Wed, 1/25/05; no data reported.

Meter experienced a battery failure.



Location: 7518 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24-1/31 Date:

75.3 dBA = Highest Measured Level

Rain occurred all day Wed, 1/26/05; no data reported.

Notes: See attached Noise Measurement Form

Date:		1/24 Mon	1/25 Tue	1/27 Thu	1/28 Fri	1/29 Sat	N30	M
-		Leq(h)	Leq(n)	Lequi	Lea(h)	Leq(h)	Leg(h)	Lea(h)
	-	dBA	dBA	dBA	GBA	dBA	GBA	ap
12:00 - 1:00	ше	1	70.4					
*	am	1	68.7	1		1		
1	am	1	67.9	1		1		
18	am	1	68.8	1		1		
1	am	1	71.5			-		•
	me	1	75.3	1		1	The state of the s	
	me	1	75.2					*
*	am	1	74.5	1		ı		
	am	1	74.3	1	1	1		•
	am	ı	74.4		1	1		•
	am	1	74.2		1	1		•
	BITT	1	75.0		ı	1		
4	Ed	1	75.0		1			•
	md	1	73.8		1			*
	Ed	1	74,1		1		•	٠
	Ed	1	74.8		ı			
	Ed	74.7	74.4		1			•
	Ed	74.1	73.5		ı			*
	Ed	73.9	73.8		1	•		
	md	74.8	75.0		t		•	•
	Ed	74.9	t	٠	1			*
00 - 10:00	Ed	74.6	1		1			1
	шд	74.1	-	The state of the s		THE STREET	The same of	+
0	ma	72.5	1	The same of				1

= Nighttime period

= No measurement, or rainy or wet period t .

= Meter experienced a battery failure

Bold exceeds extraordinary abatement criteria

PROJECT: Building Acou		ENGINEER:		DAT	
LOCATION:	City of Inglewood, CA	1	ay and	AA(0'.1(4-05
7518 Midfield Aven	ue,		7	75	NO.:
SOUND LEVEL METER: LD-870 LD-820 NL-31 LD-812 LD-2900 LD-812	MICROPHONE: NON-POLAR EI POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: ☐ LD-900B ☐ LD-828 (X 906 C		R: KBAT 🗆 A	
SERIAL #: 1502	2.0 26931 Calibration, dB:	SERIAL#:	TEMP: 64.	NS AT START OF MI	EAS.)
D LD CA250	Before 93.0 / 94 After 93.6 / 93.8	A 1111 mm 1	TOWARD (DIF R. HUMIDITY: CAMERA		
METER SETTING: A-WTD, SLOW RESPOI LEQ, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS L90, LMIN, LMAX		PHOTO NOS.		
	TLES and Thuis meter ran out	day - Bog	was ov		
SKETCH \	Freeway				
Chain		LROW		Chain Link	

71.7 dBA

Hourly Noise Levels, Leq(h)

7522 Midfield Avenue, Inglewood, CA Location:

Rear Yard Position:


1-405 Highway Traffic Sources:

Date:

1/24 - 1/31

Rain occurred all day Wed, 1/26/05; no data reported. See attached Noise Measurement Form Notes:

Automatic run timer stopped meter on Sunday at 12 noon.



Location: 7522 Midfield Avenue, Inglewood, CA

Rear Yard Position:

1-405 Highway Traffic Sourcest

Date:

1/24 - 1/31

71.7 dBA - Highest Measured Level

Rain occurred all day Wed, 1/26/05; no data reported. Notes: See attached Noise Measurement Form

Day:	1/24 Mon	1/25 Tue	1/27 Thu	1/28 Fri	1/29 Sat	1/30 Sun	1/31 Mon
	Leq(h)	dBA	Leg(h) dBA	dBA	(dBA	(dBA	Leq(h) dBA
am		66.4	1	67.6	*	69.1	
me	1	64.8	1	66.0		68.0	
me	1	64.2		65.2		67.7	
me	1	66,3	1	65,3	1	65,5	
am		67.9	1	68.1		65.3	
E	1	71.3	1	71.7		66.99	
am	1	70.6	TO THE PERSON NAMED IN	70.6		68.7	
am	1.	8.68	1	68.8	ı	69,5	٠
me	1	69.69	1	1	ı	70.4	
Ee	1	89.8	70.2	ı	1	71.2	٠
E	1	9.69	69.4	1	1	71.3	•
me	1	7.07	69.6	ŧ	ı	70.5	•
Ed	1	70.6	71.1	t	68.0		•
Ed	1	68.9	70.8	t	68.5		٠
md	1	69.0	70.5	1	68.0	*	٠
Ed	1	70.2	9.69	1	67.9	*	
Ed	70.3	688	69.7	t	69.1	•	٠
Ed	69.7	69.2	69.7	1	68.3	•	•
Ed	69.7	69,5	70.0	1	68.6		٠
md	70.5	70.0	70.3	1	70.6		٠
ELID	70.5	ı	70.7	ı	71.5	•	•
md	70.1	1	71.1	ı	71.4		1
md	668		70.8	-	71.1	*	1
E C	68.4	1	69.1	:	70.6		1

- Nightlime period


= No measurement, or rainy or wet period

Bold exceeds extraordinary abatement criteria

» Automatic run timer stopped meter on Sunday at 12 noon.

PROJECT: Building Acou Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	y and Matt	DATE: 01-24-05
Tocation: 7522 Midfield Aven	ue,		J	SITE NO.: 7522
SOUND LEVEL METER: LD-870	MICROPHONE: I NON-POLAR I POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: □ LD-900B □ LD-828 ⋈ ## - 2.	NOTES: SYSTEM PWR: □ BAT	□ AC
SERIAL#: 030	SERIAL #:	SERIAL #:	(OBSERVATIONS AT STAR TEMP: 1/2_ oF	T OF MEAS.)
CALIBRATOR: □ LD CA250 □ BK 4(55	Calibration, dB: Input Reading Before 93.8 / 93.8 After 93.8 / 93.7	TIME:	WIND SPEED: OTOWARD (DIR): R. HUMIDITY: JR 6 9	MPH
METER SETTING: A-WTD, SLOW RESPOI LEQ, L01, L10, L25, L50,	NSE, 1 HOUR INTERVALS Leo, LMIN, LMAX		PHOTO NOs.	
	TES:			

ST	ART	NOTES:						
DATE	DIME	Home	DOWNER	was	TON	nome	401	pick-up
01-24-05	3:00	1300316		THE PARTY OF				,
ST	TOP							
DATE	TIME	1						
1-30-6	12:00 -	+Timet	torned	off				



76.3 dBA

Hourly Noise Levels, Leq(h)

7528 Midfield Avenue, Inglewood, CA Rear Yard Location:


Position:

1-405 Highway Traffic Sources:

Date:

See attached Noise Messurement Form Notes:

Rain occurred all day Wed, 1/26/05; no data reported



Appendix D

Hourly Noise Levels, Leq(h)

Location: 7528 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24-1/31 Date:

76.3 dBA = Highest Measured Level

Rain occurred all day Wed, 1/26/05; no data reported. Notes: See attached Noise Measurement Form

	Sun Mon	_		100									_		_	_		_					_				73.3
1/29	Sat	Lequi	dBA	1					1	-	1	1	1	1	t	71.8	72.4	72.1	71.8	72.7	7.17	72.0	73.8	74.6	74.6	74.3	73.8
1/28	Fri	Leg(h)	dBA	71,1	69.3	68.8	68.8	71.5	75.2	75.3	73.4	1	1	1	t	1	1	1	1	1	ı	1	1	1		1	1
1/27	Thu	Leq(h)	dBA		1	1			1	1	1	ı	74.2	74.9	75.0	76.3	75.9	75.8	74.8	74.9	7.4.7	73.9	74.0	74.5	74.8	74.4	72.7
1/25	Tue	Leq(h)	dBA	6'69	68.2	67,5	68.5	71.2	74.7	74,4	73.6	73,4	73,5	73.4	74.2	74.3	72.9	73.1	74.1	73.7	72.9	73.2	73.7	1	ı	1	
1/24	Mon	Leq(h)	dBA	1		1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	73.2	74.1	74.1	73.8	73.4	71.8
32				am	am	me	am	am	me	me	me	E	am	E	E	md	Ed	E d	md	Ed	md	Ed	Ed	Ed	md	ша	ma
Date	Day:		TIME				*	1				*								*	5:00 - 6:00		*		*		


= Nighttime period

No measurement, or rainy or wet period

Bold exceeds extraordinary abatement criteria

PROJECT: Building Acou- Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	E.T.	DATE: 01-24-05
LOCATION: 7528 Midfield Aven	ue,			SITE NO.: 7528
SOUND LEVEL METER: 5 LD-870	MICROPHONE: ANON-POLAR II POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIRD SCREEN BK 4199	PRE AMP: ☐ LD-900B ☐ LD-828 ☑ 100 ←	SYSTEM PWR:	(BAT [] AC
SERIAL #: 120	SERIAL #: 2021 350	SERIAL #:	TEMP: 63	F
CALIBRATOR: LD CA250 A 4155	Calibration, dB: Input Reading Before 114.0 / 114.3 After 114.9 / 114.2	5130P G140P	WIND SPEED: CO TOWARD (DIR): R. HUMIDITY: 7	_
METER SETTING: A-WTD, SLOW RESPON LEQ, Lot, L10, L25, L50, I	NSE, 1 HOUR INTERVALS 190, LMIN, LMAX		РНОТО NOs	3, 14,15

91	ART	NOTES:	12 44		MIT .					Harl
DATE	TIME		20 m	LN I	MEAS	W/VIE	KO	5:30-	5.50	1/24/05
01-24-05	18,00	LEQ	LMAX	LI	LID	L25	L50	L90	199	LMIN
81	ГОР	-	-	-			-	-	-	_
DATE	TIME	73.0	81,6	75.7	74.0	736	72.9	71.8	70,7	70,3
		COVEN	ed mion	ophene:	1/25 194	5 una	m bern	coopline:	wak (n	renge)



73.3 dBA

Hourly Noise Levels, Leq(h)

7538 Midfield Avenue, Inglewood, CA Location:


Rear Yard

1-405 Highway Traffic Position: Sources:

Date:

See attached Noise Measurement Form Notes:

Rain occurred all day Wed, 1/26/05; no data reported.



Location: 7538 Midfield Avenue, Inglewood, CA

Rear Yard Position:

Sources: 1-405 Highway Traffic

1/24 - 1/31 Date:

73.3 dBA = Highest Measured Level

See attached Noise Measurement Form Notes:

Rain occurred all day Wed, 1/26/05; no data reported.

Date: Day:	19 17	1/24 Mon	1/25 Tue	1/27 Thu	1/28 Fri	1/29 Sat	1/30 Sun	1/31 Mon
TIME		Leq(h) dBA	Leq(h) dBA	Leg(h) dBA	Leq(h) dBA	Length) dBA	Leq(h) dBA	dBA dBA
0 - 1:00	ams		62.9*	1	68.7	1	7.07	0.69
	am	1	61.3*	1	67.0	1	69.5	8.99
*	am		61.0*	1	66.4	1	69.3	65.7
0 - 4:00	me	1	62.1*	-	66.4	-	67.1	67.2
	me		64.7"		69.2	1	66.8	6.69
00:9 - 0	am		67.7*		72.9	1	68.4	73.3
	am		.66.9*	,	72.3	1	70.2	73.2
7:00 - 8:00	am	1	65.7+	1	70.6	1	7.0.7	70.8
00:6 - 0	am	ı	6.57*	1	ı	t	7.1.7	70,4
. *	am	,	69.7	70.4	1	1	72.5	71.5
0 - 11:00	me	į	71,5	70.9	ı	1	72,6	71.0
	ше	ı	72.3	71.3	1	1	72.0	70.9
	Ed	1	72.0	72.5	1	69.8	70.4	71.1
*	md	ı	7.07	72.0	1	70.2	89.8	71.9
	Ed	1	71.0	72.0	1	69.6	69.5	72.1
*	md	ı	7.17	71.1	:	69.7	69.5	70.9
	End	70,8	71.3	71.3	1	70.9	71.3	71.3
	md	-66.0*	70.4	71.3	t	70.1	71.4	71,8
	md	-66.0*	7.0.7	71.3		70.5	70.9	71.5
	Ed	-0'29	71,2	71.9	1	7.9	72.6	72.2
	ш	.66.5*	1	72.0	t	72.8	73.3	72.9
9:00 - 10:00	ша	66.2*	1	72.2	1	72.8	72.9	1
0:00 - 11:00	md	66.2*	1	72.0	1	72.5	72.0	1
9	ша	64.5*	1	70.2	1	72.0	71.0	1


= Nighttime period

= No measurement, or rainy or wet period

Bold exceeds extraordinary abatement oriteria

= Wind blew microphone tripod over on ground during this period

PROJECT: Building Acoust Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	ay and Mart	DATE: 01-24-05
TOCATION: 7538 Midfield Aven	ue,)	SITE NO.: 7538
SOUND LEVEL METER: XLD-870	MICROPHONE: NON-POLAR D POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: □ LD-900B □ LD-828 □ LD-900C		
SERIAL #: 162_	SERIAL #: 84K 4176 206932	3813	TEMP: 66. PF	
CALIBRATOR: □ LD CA250 ⋈ BK 4155	Calibration, dB: Input Reading Before 93.8 / 93.9 After 93.6 / 93.9	9:35 8:36	WIND SPEED: O TOWARD (DIR): R. HUMIDITY: 100 % CAMERA ACEATEC	
METER SETTING: A-WTD, SLOW RESPON LEQ, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS L90, LMIN, LMAX		PHOTO NOs.	



Location: 7542 Midfield Avenue, Inglewood, CA

Position: Rear Yard


Sources: I-405 Highway Traffic

Date: 1/24 - 1/31

75,2 dBA = Highest Measured Level

Notes: See attached Noise Measurement Form Rain occurred all day Wed, 1/25/05; no data reported.

Automatic run timer stopped meter on Sunday at 12 noon.



Location: 7542 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24 - 1/31 Date:

75.2 dBA = Highest Measured Level

See attached Noise Messurement Form Notes:

Rain occurred all day Wed, 1/26/05; no data reported.

1/31	Mon	Ceg(h)											٠												1		1
1/30	Sun	Leg(h)	79.5	200	11.4	71.1	68.8	68.7	70.3	72.1	72.7	73.7	74.6	75.0	74.6											N 1100	
1/29	Sat	Lea(h)	200		1	1		1			1	,	ı	:	ı	72.4	73.0	72.5	72.4	73,3	72.2	72.7	73.9	7.4.7	74.7	74.4	73.9
1/28	Fri	Leg(h)	010	7.1.0	69.2	68.8	68,8	71.4	75.0	74.5	73.4	1	t	ı	1	t	ı	1	1	1	ı	ì	1	1		1	1
1/27	Thu .	Leg(h)	Ago		1	t	t		1	1	1	1	73.2	73.9	74.2	75.2	74,5	74.6	73.7	76.4**	73.4	73.4	78.5**	74.3	74.5	74.2	72.4
1/25	Tue	Leq(h)	ADD	0.00	68.3	67.8	68.7	71.4	74.8	74.6	74.0	73.9	74.1	74.0	74.8	74.6	73.5	73.7	74.2	73.8	72.9	73.2	74.1	1	1		
1/24	Mon	Laqh)	day			-		,			1	1	1	1		ı	1	1	t	74.1	73,4	73.3	74.2	74.2	73.9	73.5	71.8
22		_		am	am	am	am	me	arm	am	am	Es	Ee	am	am	md	Ed	Ed	md	md	md	md	Ed	md	Ed	mid	ша
Date:	Day	-	IME	200	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00
		ľ	20.00	12:00	1:00	2:00 -	3:00 -	4:00 -	5:00 -	6:00	7:00	8:00 -	9:00	10:00	11:00 -	12:00 -	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00 -

^{* * =} Non-traffic related noise = Nighttime period

1 .

⁼ No measurement, or rainy or wet period

Bold exceeds extraordinary abatement criteria

⁼ Automatic run timer stopped meter on Sunday at 12 noon.

eld Avenu IETER: LD-820 LD-812	MICROPHONE: NON-POLAR POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN SERIAL #:	PRE AMP: □ LD-900B □ LD-828	Ray and Mart	5ITE NO.: 7542
LD-820 LD-812	☐ NON-POLAR ☐ POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	□ LD-900B □ LD-828		
36	SERIAL #:	风NH-21	SYSTEM PWR: BAT	
	CONTRACTO	SERIAL #:	(OBSERVATIONS AT START OF	OF MEAS.)
A250 5.5	Calibration, dB: Input Reading Before 93.8 / 93.9 After 93.8 / 93.8	TIME:	The state of the s	1PH
NOT	ES:			
ME - I	tome owner not	home di	ving pick-up.	
00			6 13	
ME				
111111111111111111111111111111111111111	mer stooms			
	23'	m.s'		
	NOT - I	NOTES: HOME OWNE! NOT ME OD TIMES STOPPEL Shrubs	NOTES: - Home owner not home du Shrubs 123' TMS'	NOTES: - HOME OWNER NOT home during pick- up. ME OD TIMES STORPEL Shrubs

72.1 dBA

Hourly Noise Levels, Leq(h)


7548 Midfield Avenue, Inglewood, CA Rear Yard 1-405 Highway Traffic 1/24 - 1/31 Location:

Position:

Sources Date:

See attached Noise Measurement Form Notes:

Rain occurred all day Wed, 1/26/05; no data reported.



Appendix D

72.1 dBA - Highest Measured Level

Hourly Noise Levels, Leq(h)

Location: 7548 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

Date: 1/24-1/31

Notes: See attached Noise Measurement Form

Rain occurred all day Wed, 1/26/05; no data reported.

1/31	Mon	(d)ber	dBA	87.8	65,4	64.3	65.5	68.5	71.8	7.17	69.7	69.5	70.4	70,1	69.9	70.2	70.8	70.7	69.7	66.69	70.8	70.3	70.8	71.6	1		1
1/30	Sun	Lea(h)	dBA	69.2	68.3	87.8	9.99	65,5	6.69	68.9	69.5	70.6	71.3	71.6	71.2	69.6	69.1	68.7	68.7	69.7	68.8	69.7	7.17	72.1	71.8	70.8	70.0
1/29	Sat	Leg(h)	dBA		1			1		-	1	1	1	1	t	69.1	69.5	68.9	0.69	70.0	69.0	69.3	71.0	71.8	71.8	71.4	70.8
1/28	F	Leght	dBA	67.7	65.7	66.3	65.2	67.9	71.6	71.1	71.2	ı	1	1	t	1	:	1	t		1	ı	:	1	ı	4	1
1/27	Thu	Leg(h)	dBA	1	1	3	,	1	1	1	1	ı	71.6	70.3	70.6	7.17	71.0	71.0	70.2	70.2	70.3	70.5	71.0	71.3	71.4	6'02	69.2
1/25	Tue	Leq(h)	dBA	66.5	64.9	64.4	65.3	68.0	71.5	71.4	70.6	70.5	70.6	70.5	71.3	71.2	66.69	70.2	70.8	70.6	69.8	70.1	70.4	ı	t	1	-
1/24	Mon	Leg(h)	dBA	1	1	1	1	1	1	1	1	ı	1	ı	1	1	1	1	1	70.8	70.3	70.2	70,8	70.8	70.5	70.1	68.5
200	,,,			am	E	am	E	ВШ	me	am	me	am	am	me	am	md	Ed	md.	md	Ed	Ed	md	Ed	Ed	md	md	H _d
Date	Day:	The said	TIME	1:00	2:00	3:00	4:00	5:00	9:00	7:00	8:00	9:00	10:00	11:00	12:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00
				2:00 -	1:00 -	2:00 -	3:00 -	4:00 -	5:00 -	- 00:9	7:00 -	8:00 -	- 00:6	- 00:0	1:00	2:00 -	1:00	2:00 -	3:00 -	4:00 -	5:00 -	6:00 -	7:00 -	8:00	9:00	00:00	1:00 -


= Nighttime period

- = No measurement, or rainy or wet period

Bold exceeds extraordinary abstement criteria

PROJECT: Building Acous Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	Ray and Mart	DATE: 01-24-05
T548 Midfield Aven	ue,			SITE NO.: 7548
SOUND LEVEL METER: LD-870 LD-820 NL-31 LD-812 LD-2900 LD-812	MICROPHONE: XNON-POLAR [] POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: XLD-900B LD-828	SYSTEM PWR: X BAT	
SERIAL#: 161	SERIAL #: 5K 4159 228197-6	SERIAL#:	TEMP: 61.8 F	
CALIBRATOR: □ LD CA250 □ LK 4195	Calibration, dB: Input Reading Before 93.6 / 93.9 After 93.6 / 93.8	10:49 9:42	TOWARD (DIR): R. HUMIDITY: 64,2 % CAMERA	APH
METER SETTING: A-WTD, SLOW RESPON LEQ, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS L90, LMIN, LMAX		PHOTO NOs.	

ST	ART	NOTES:				72	1			4 14
DATE	TIME	wind	Screen	was	NOT O	n me	ter.	TT	was	Inside
01-24-05	10:52		plasti							
DATE	TIME	l'								
1-1-05	9:41	Home	owner	was	HOT	nome	durin	9 1	ick-v	P



69.9 dBA = Highest Measured Level

Hourly Noise Levels, Leq(h)

7552 Midfield Avenue, Inglewood, CA Location:


Rear Yard Position:

1-405 Highway Traffic Sources:

Date:

See attached Noise Messurement Form Notes:

Rain occurred all day Wed, 1/26/05; no data reported.



Location: 7552 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: I-405 Highway Traffic

1/24-1/31 Date:

69.9 dBA = Highest Measured Level

See attached Noise Measurement Form Notes:

Rain occurred all day Wed, 1/26/05; no data reported.

1/31	Mon	Leg(h)	dBA	64.6	62.0	61,5	63.0	65,1	68.3	67.6	64.7	64.0	85.1	64.2	63.4	63.9	64.7	64,4	63.6	64,6	66.6	66.8	67.1	68.2	1		
1/30	Sun	Legiti	dBA	65.7	65.0	64.2	61.8	619	63.6	65.5	65.7	65.9	66.2	68.6	65.7	63,2	62.9	62.6	62.5	63.7	64.7	65.5	67.2	68.8	68.3	67.4	67.0
1/29	Sat	Leq000	dBA	+	1				1	1	ı	1	1	1	t	65.1	64.5	83.5	65.0	72.3*	699	68.9	69.3	666	69.7	69.1	68:3
1/28	Fri	[red(h)	dBA	63.6	61.8	80,8	61.1	63.5	67.4	66.2	64.4	1	t	1	ï	1	1	1	ı	ı	1	1	1	t	1	1	1
1/27	Thu	Leq(h)	dBA	1	1	t		1		1	1	1	63,8	64.4	65.0	96.5	65.6	65.7	64.7	66.0	65.8	66.8	67.0	67.0	67.2	66.7	65.1
1/25	Tue	Leq(n)	dBA	61.7	9'09	60.3	61.5	63.7	67.2	66.2	65.0	64.7	64.7	64.3	68.2	65.0	63.4	65.0	62.9	65.4	65.1	65.9	65.4	1	1	1	1
1/24	Mon	Leq(h)	dBA	1	1			1	1		:	:	ŧ	1	ı	1	1	t	ı	62:3	65,6	85.8	65.5	65,5	65.2	65.2	63.9
120	**			am	am	BTTH	am	am	me	am	am	ше	Es	шв	am	Ed	ш	Hd	md	md	Elid	Ed	md	md	md	ши	md
Date	Day:		TIME	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00
			473	2:00 -	1:00 -	2:00 -	3:00 -	4:00 -	5:00 -	- 0009	7:00 -	8:00 -	- 00:6	- 00:01	1:00 -	2:00 -	1:00 -	2:00 -	3:00 -	4:00 -	5:00	6:00 -	7:00 -	8:00 -	9:00	10:00	11:00 -

= Nightlime period


- No measurement, or rainy or wet period

= Non-traffic related noise

Bold exceeds extraordinary abatement criteria

PROJECT: Building Acous Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	and Mart	DATE: 01-24-05
7552 Midfield Aven	ue,	J		SITE NO.: 7552
SOUND LEVEL METER: LD-870 LD-820 NL-31 LD-812 LD-2900 LD-812	MICROPHONE: O(NON-POLAR POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN BK 4176	PRE AMP: CLD-900B LD-828	SYSTEM PWR: DEBAT	
SERIAL#: 163	SERIAL #: 2076930	SERIAL #:	TEMP: 12,7 "F	and the same
CALIBRATOR: □ LD CA250 □ RK AI 95	Calibration, dB: Input Reading Before 93.8 / 93.8 After 93.5 / 93.7	TIME: 2;22	WIND SPEED: 2 TOWARD (DIR): FIRE W R. HUMIDITY: 65.5 %	all
METER SETTING: A-WTD, SLOW RESPON LEQ, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS 190, LMIN, LMAX		PHOTO NOs.	

ST	ART	NOTES:	2 SWITTER		o a Same	- 0.0	fri-off@ 4:00
DATE	TIME	PYON	Tues	011	west	04	Tri -07+ @ 4,00
01-24-05	2:35						
S	TOP						
DATE	TIME						



74.8 dBA

Hourly Noise Levels, Leq(h)

Location: 7558 Midfield Avenue, Inglewood, CA

Position: Rear Yard


Sources: 1-405 Highway Traffic

1/24 - 1/31

Date:

Notes: See attached Noise Measurement Form

Rain occurred all day Wed, 1/26/05; no data reported.



Appendix D

Hourly Noise Levels, Leq(h)

Location: 7558 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24 - 1/31 Date:

74.8 dBA = Highest Measured Level

Notes: See attached Noise Measurement Form Rain occurred all day Wed, 1/26/05, no data reported.

1/25 Tue	S e S		1/27 Thu	1/28 Fri	Sat Leon	1/30 Sun	Mon Leathi
dBA	IA IA	_	dBA	dBA	dBA	dBA	dBA
69.6	9		1	7.07		72.0	7.0.7
68.0	0	-		69.0	1	7.07	68.5
67.5	10			68.6		70.8	67.4
68.5	10		1	68.7	1	68.7	68.9
71.2	tvi			71.4	1	68.5	71.8
74.5	un			74.8	1	70.0	74.8
74.3	02		1	74,4		74.7	74.8
73.6	10		t	72.7	1	72.3	72.7
73.6	10	_	1	1	1	73.3	72.5
73.7	1		73.0	1	ı	74.0	73.2
73.6	9		73.4	ı	1	74.1	72.9
74.2	ru.		73.5	t	1	73.8	73.1
74.0	0		74.4	1	71.4	72.6	73.3
73.0	0		73.9	1	72.0	72.1	73.7
73.1	-		73.9	t	71.7	71.9	73.9
73.6	10		73.3	1	71,4	71.8	72.7
73.2	c4		73.1	1	72.2	72.8	72.8
72.2	e4		72.8	1	71.4	73.0	73.1
72.5	in		72.9	1	71.8	72.4	72.9
73.3	63		73,4	1	73.0	74.0	73.8
1			73.9	t	73.9	74.5	74.2
1			74.0	1	73.8	74.3	1
-		Ī	73.9	+	73.6	73.5	1
1			72.1	1	73.1	72.5	1

= Nighttime period

No measurement, or rainy or wet period
 Annutralise activity.

= Non-traffic related noise

Bold exceeds extraordinary abatement oriteria

PROJECT: Building Acoust Near I-405 in the C	ical Study for Houses lity of Inglewood, CA	Mati	- and	Ray	DATE: 01-24-05
LOCATION: 7558 Midfield Avenu	e,			٦	SITE NO.: 7558
SOUND LEVEL METER: D LD-870	MICROPHONE: KNON-POLAR II POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: A LD-900B LD-828	200.00000000000000000000000000000000000	WR: KBAT	
SERIAL#: 159	SERIAL #: 2145107	SERIAL #: 3809	TEMP: 68		OF MEAS.)
CALIBRATOR:	Calibration, dB: Input Reading Before 98.8 / 94	TIME:	TOWARD (D R. HUMIDIT)		MPH
A BK 4155	After 93.9/93.88	12:01	CAMERA _		
METER SETTING: A-WTD, SLOW RESPONS LEQ, L01, L10, L25, L50, L9				-	
DATE TIME 1-1-05 (1:40	Free wo	U			
SKETCH	Tree was	1			
Nieghbors 1	22!	Green			8/44
Goioge Wrall=11	House	Ð			

7562 Midfield Avenue, Inglewood, CA Rear Yard


Location: Position:

1-405 Highway Traffic Sources:

2/28 - 3/4/2005 Date:

= Highest Measured Level 70.9 dBA

See attached Noise Measurement Form Heavier rains occurred on Wed. and Fri. Notes:



70.9 dBA * Highest Messured Level

Location: 7562 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

Date: 2/28 - 3/4/2005

Notes: See attached Noise Measurement Form Heavier rains occurred on Wed. and Fri.

3/4	100	Leag(h)	700	000	64.7	64,4*	ī	-	1	1	1	69.0	69.2	1	í	I	1	1	1	1	1	1	1	1	1	1	1
3/3	nui	Leq(h)	Yan	1	61.6	61.7	62.5	65.3	67.8	67.8	67.3	66.4	68.1	87.8	66.9	66.4	65.8	65.3	629	66.2	66.5	66.3	68.0	68.7	69.4	69.1	87.8
3/2	Ned	Leq(h)	WOD	66.4	65.2	64.1	65.0	87.5	70.9	70.1	68.6	67.9	67.5	66.99	87.8	67.4	68.1*	67.5*	66.9	.8.99	ı	ı	1	1	ı	-	1
3/1	901	Leq(h)	AGD	66.0	84.8	63.9	64.6	67,3	7.07	70,1	68.7	68.8	68,6	68.3	68.1	87.8	67.8	6.99	66.9	67.0	66.9	66.2	6.89	68.2	69.3	69.2	67.3
2/28	Mon	Leq(h)	dBA	1	1		1	1.			1	ı	1	ı	68,2*	67.5	87.7	87.8	68.7	67.4	68.6	68.4	69.0	69.3	69,2	68.7	67.4
:			1	am	am	am	am	am	am	am	am	am	am	am	am	Ed	md	Ed	md	md	md	ш	md	md	md	md	md
Date:	Day:	-	1	2:00 - 1:00	:00 - 2:00	2:00 - 3:00	3:00 - 4:00	4:00 - 5:00	5:00 - 6:00	6:00 - 7:00	7:00 - 8:00	8:00 - 9:00	9:00 - 10:00	10:00 - 11:00		12:00 - 1:00	:00 - 2:00	2:00 - 3:00	4	4:00 - 5:00	5:00 - 6:00	6:00 - 7:00	7:00 - 8:00	8:00 - 9:00	9:00 - 10:00	10:00 - 11:00	1:00 - 12:00


= Nighttime period = = No measurement, or rainy or wet period

Bold exceeds extraordinary abatement criteria

• = Light rain, no adverse effect on measurement

PROJECT: Building Acous Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	MATT	DATE: 02-28-05
LOCATION: 7562 Midfield Avenu	ue			SITE NO.: 7562
SOUND LEVEL METER: LD-870 LD-820 NL-31 LD-812 LD-2900	MICROPHONE: WHON-POLAN CI POLARIZED 1/2-INCH RANDOM PHOIDENGE W/ WIND SCREEN	PRE AMP: 55 LD-9006 D LD-828	SYSTEM PWR: 2 BAT	
SERIAL #: 0159	2145107	SERIAL #: 3809	TEMP: 70.2 F	and the second second
CALIBRATOR: □ LD CA250 □ EAKA155	Calibration, dB: Input Reading Before 94.0 / 94.0 After 94.0 / 93.6	11:28 A 9:21 A	WIND SPEED: TOWARD (DIR): R. HUMIDITY:@2_% CAMERA	MPH
METER SETTING: A-WTD, SLOW RESPON LEQ, L01, L10, L26, L50, L	ISE, 1 HOUR INTERVALS		PHOTO NOs.	

ST	ART	NOTES:	
DATE	TIME		
02-28-06	11:00 A		
	ГОР		
DATE	TIME		
03-84-05	9120A		



7568 Midfield Avenue, Inglewood, CA Location:

Rear Yard Position:

1-405 Highway Traffic Sources:


1/24 - 1/31

Date:

= Highest Measured Level 75.4 dBA

See attached Noise Measurement Form Notes:

Rain occurred all day Wed, 1/26/05; no data reported. A/C power failure on Sunday.



Location: 7568 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24 - 1/31 Date:

75.4 dBA = Highest Measured Level

Notes: See attached Noise Measurement Form

Rain occurred all day Wed, 1/26/05; no data reported.

1/31	Mon	Leq(h)	dBA						*			•									٠				t	1	1
1/30	Sun	(red))	dBA	72.7	71.6	71.1	69.1	69.1	70.5	72.4	73.0	73.6							•			•					1000000
1/29	Sat	Legino	dBA	1		1		1		1	1	ı	1	1	1	73.0	73.4	72.9	72.9	73.9	72.8	73.2	74.6	75.2	75.2	7.4.7	74.1
1/28	Fri	Leg(h)	dBA	71,1	69.3	0.69	0.99	71.5	75.0	74.8	73.2	1	t	1	1	1	1	t	t	t	1	1	1	t	1	1	1
1/27	Thu	Leg(h)	dBA		1	1	1	-	1		:	:	73.7	74.3	74.7	75.4	74.8	74.9	74.2	74.0	73.9	74.0	74.3	74.8	74.9	74.3	72.6
1/25	Tue	Leght	dBA	70.0	68.4	67.9	68.9	71.6	75.0	74.9	74.2	74.2	74.3	74.3	75.0	74.8	74.0	74.1	74.6	74.2	73.3	73.6	76.0**	t	1	1	1
1/24	Mon	Leq(h)	dBA				-		1	1		1	1	1	;	1	1	1	1	74.5	74.0	73.7	74.3	74.2	73.9	73,5	71.9
11				am	aim	am	am	am	am	am	am	вт	ше	am	am	md	md	md	md	md	md	md	md	ш	md	ша	md
Date	Day:		TIME	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00
				12:00 -	1:00 -	2:00 -	3:00 -	4:00 -	5:00 -	6:00	7:00 -	8:00 -	9:00	10:00	11:00	12:00 -	1:00 -	2:00 -	3:00 -	4:00	5:00 -	6:00 -	7:00 -	8:00	9:00	10:00	11:00 -

^{* * =} Non-traffic related noise = Nighttime period

Bold exceeds extraordinary abatement criteria

⁼ No measurement, or rainy or wet period

⁼ A/C power failure on Sunday 1 .

PROJECT: Building Acou Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	т	DATE: 01-24-05
LOCATION: 7568 Midfield Aven	ue,			SITE NO.: 7568
SOUND LEVEL METER: LD-870	MICROPHONE: I) NON-POLAR (C) POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: DI LD-900B LD-828	NOTES: SYSTEM PWR: BAT	D/AC
SERIAL#: 049/p	SERIAL #: 220V	SERIAL 0:	(OBSERVATIONS AT START TEMP: 4 *F	
CALIBRATOR: D'LD CA250	Calibration, dB: Input Reading Before \\\\ \(\lambda 0 f \\\ \(\lambda 0 \) After \\\\\ \(\lambda 1 \\\ \\ \(\lambda 1 \\\ \(\lambda 1 \\\ \\ \(\lambda 1 \\\ \\ \(\lambda 1 \\\ \(\lambda 1 \\\ \\ \(\lambda 1 \\\ \\ \\ \(\lambda 1 \\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	TIME:	WIND SPEED: 0.9 1 TOWARD (DIR): R. HUMIDITY: 67 % CAMERA ET	MPH
METER SETTING: A-WTD, SLOW RESPO! LEG, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS Leo, LMIN, LMAX		PHOTO NOs. 2	

	ART	MOTES: miche ohome 1/25 1935 uncouned microphone: unlangum (no mano)
DATE	TIME	correct micro phone 1/25 1935 uncoured unicrophone: unlamour (no mone)
01-24-05	LOSDOA	unicrophore uncomered 1/1 upon netricial
5	TOP	muter stopped 30 Jan 2005 @ 0840
DATE	TIME	may sighes so an mas in part

SKETCH		5	ME (om	er states	to be two do	men, talon mut)
	-	-X	¥	- 11	- Y &	-> 145'WF
	×				11.00	4' mw (cached)
	551MW				78'	LES'MW
	-1	1/8			V	€ b' MW
	*					j
	1929	7				×
	1	600			8	
			7568			1

= Highest Measured Level

72.5 dBA

Hourly Noise Levels, Leq(h)

Location: 7572 Midfield Avenue, Inglewood, CA


Position: Rear Yard

Sources: 1-405 Highway Traffic

Date: 1/24 - 1/31

Notes: See attached Noise Measurement Form Rain occurred all day Wed, 1/26/05; no data reported.

Automatic run timer stopped meter on Sunday at 12 noon.



72.5 dBA = Highest Measured Level

Hourly Noise Levels, Leq(h)

Location: 7572 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24-1/31 Date:

Notes: See attached Noise Measurement Form

Rain occurred all day Wed, 1/26/05; no data reported.

1/31	Mon	Leq(h)	dBA	· ·		-																*			ŧ	THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN CO	
1/30	Sun	Leghi	dBA	0.69	67.9	67.4	65.3	65.2	8.99	68.7	69.2	70.0	70.5	70.7	71.2												STATE OF STATE OF
1/29	Sat	Leg(h)	dBA	1	t	1		1	1	1	1	1	ı	1	ı	68.6	68.3	67.6	68.6	70.4	69.5	6669	7.1.7	72.5	72.3	71.7	71.1
1/28	Fri	Leg(h)	dBA	67.3	65.6	64.7	64.9	67.6	71.4	70.4	68.3	-	1	1	t	1	t	t	1	1	1	1	1	t	1	1	
1/27	Thu	Leq(h)	dBA		1	*	1			1	1	1	68.5	68.8	69.3	70.6	69.8	6.69	69.2	69.5	69.7	70.1	70.3	70.6	70.8	70.5	68.7
1/25	Tue	Leg(t)	dBA	65.8	64.4	64.0	65.1	67.6	71.0	70.4	69.3	69.2	69.3	69.1	70.4	89.8	68.3	68.8	69.6	69.5	68.8	69.4	69.5	1	1	E	1
1/24	Mon	Leq(h)	dBA	1	-	1	-	1	1	-	1	1	1	1	1	1	1	1	ı	70.1	49.7	69.8	70.0	69.8	69.5	69.4	67.9
12	**	_		Bm	am	am	am	am	BITTE	am	BITT	am	BITT	am	am	md	md	md	md	md	md	End	md	шф	ш	md	md
Dete	Day:		TIME	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00
			7.	2:00 -	1:00 -	2:00 -	3:00 -	4:00 -	5:00 -	- 00:9	- 00:4	8:00 -	9:00 -	- 0000	1:00 -	2:00 -	1:00 -	2:00 -	3:00 -	4:00 -	5:00 -	6:00 -	7:00 -	8:00 -	- 00:6	- 00:0	1:00


= Nighttime period


Bold exceeds extraordinary abatement criteria

1 .

No messurement, or rainy or wet period
 Automatic run timer stopped meter on Sunday at 12 noon.

PROJECT: Building Acou Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	Day and Mart	DATE: 01-24-05
T572 Midfield Aven	ue,			SITE NO.: 7572
SOUND LEVEL METER: LD-870 LD-820 NL-31 LD-812 LD-2900	MICROPHONE: INON-POLAR ID POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: ☐ LD-900B ☐ LD-828 ☐ LD-828	SYSTEM PWR: MEAT	□ AC
SERIAL #: 346	SERIAL #:	SERIAL #: 01553	TEMP: 72.5	
CALIBRATOR: LD CA250 K BK	Calibration, dB: Input Reading Before 93.8 / 93.9 After 93.8 / 93.8	1:27 1:15	WIND SPEED: O TOWARD (DIR): R. HUMIDITY: 4 % CAMERA	MPH -
METER SETTING: A-WTD, SLOW RESPON LEO, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS L90, LMIN, LMAX		PHOTO NOs.	_
the state of the s	TES:	1	uma Le diction	0





= Highest Messured Level

dBA

72.8


Hourly Noise Levels, Leq(h)

7578 Midfield Avenue, Inglewood, CA Location:

Position:

Rear Yard I-405 Highway Traffic 1/24 – 1/31 Sources: Date:

See attached Noise Measurement Form Notes:



= Highest Measured Level

72.8 dBA

Hourly Noise Levels, Leq(h)

Location: 7578 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

Date: 1/24-1/31

Notes: See attached Noise Measurement Form

Rain occurred all day Wed, 1/26/05; no data reported.

Date:	Day		TIME		1:00 - 2:00			15										2:00 - 3:00									1
16	25			me	E	me	Es	E	ams	am	Ee	E	E	E	E	End	Ed	E	md	End	md	md	md	md	md	md	md
1/24	Mon	Leq(h)	dBA	1		1	1	1	1	1	1	ı	1	ı	1	1	1	1	t	70.6	70.1	70.1	70.4	70.2	669	69.7	68.2
1/25	Tue	Leq(h)	dBA	66.3	64.8	64.5	66.5	68.2	71.5	70,8	69.8	8,69	66.69	69,8	71.1	70.5	69.1	69.5	70.3	70.2	69,5	66.69	70.1	া	1	1	1
1/27	Thu	Leq0i	dBA	1	-				1		1	ı	69.1	69.5	70.0	71.3	70.6	70.6	70.0	70.2	70.3	70.6	70.8	71.1	71.3	70.9	69.1
1/28	F	Laq(h)	dBA	67.7	699	66,3	65.5	68.2	71.9	70.9	68.8	ı	ı	1	1	t	ı	1	1	1	t	ı	r	t	1	1	
1/29	Sat	Leq(h)	dBA	1	1	1		1	1	-	1	1	1	1	1	69.3	68.9	68.1	69.1	70.9	68.9	70.5	72.1	72.8	72.6	71.9	71.3
1/30	Sun	Leg(h)	dBA	69.3	68.3	67.7	65.7	65.7	67.2	0.69	69.6	70.4	71,0	71.3	70.6	68.6	68.1	68.0	68.2	69.2	69.5	69.6	71.2	72.1	71.9	71.0	70.1
1/31	Mon	Leagn	dBA	8,78	85.6	84,8	88.3	689	72,1	71.6	69.5	69.0	69.9	69.4	68.2	69.6	70.4	70.5	8.69	8.69	70.9	70.8	71.1	71.8	:	1	-

= Nighttime period

- No measurement, or rainy or wet period

Bold exceeds extraordinary abatement criteria

	stical Study for Houses City of Inglewood, CA	ENGINEER:	ET	DATE: 01-24-05
LOCATION: 7578 Midfield Aven	ue,			SITE NO.: 7578
SOUND LEVEL METER: LD-870	MICROPHONE: S HON-POLAR ID POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: LD-900B LD-828	SYSTEM PWR: IF	Manager Company
SERIAL #: 0\24	SERIAL #: 204 8447	SERIAL #:	(OBSERVATIONS AT S	TART OF MEAS.
CALIBRATOR:	Calibration, dB: Input Reeding Before 14,0 / 14.0 After 14.0 / 113.9	1545 0950	WIND SPEED: 0 TOWARD (DIR): 8 R. HUMIDITY: 8	_%
METER SETTING: A-WTD, SLOW RESPON LEQ, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS		PHOTO NOs.	
SKETCH X	35' Wf includes 2 Dec	^ ^	× × × × × × × × × × × × × × × × × × ×	× 6'mw
SKETCH X WITH 21 latitle (wrid) M top	251	^ ^	Z9'	X Lb'mw
6' MW 2 with 2' lattice (world)	35' Dec	^ ^	× × × × × × × × × × × × × × × × × × ×	X Lo'mw

70.7 dBA = Highest Measured Level

Hourly Noise Levels, Leq(h)


7600 Midfield Avenue, Inglewood, CA Location:

Rear Yard Position:

1-405 Highway Traffic 1/24 - 1/31 Sources:

Date:

See attached Noise Measurement Form Notes:



Location: 7600 Midfield Avenue, Inglewood, CA.

Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24 - 1/31 Date:

70.7 dBA = Highest Measured Level

See attached Noise Messurement Form Notes:

Rain occurred all day Wed, 1/26/05; no data reported.

1/31	Mon	Leq(h)	dBA	66.4	64.3	63,3	64.8	87.8	7.07	70.2	68.2	67.9	68.7	68.2	68.0	68.3	69.1	69.4	68.4	68.6	69.5	69.2	69.8	70.1	t		1
1/30	Sun	Leagh)	dBA	87.8	66.7	66.3	642	64.3	65.8	67.5	68.1	69.2	69.8	69.8	69,4	67.4	67.0	6.89	67.2	68.2	68,4	68.2	69.7	70.4	70.4	69.5	68.4
1/29	Sat	Leqivi	dBA				1	1			1	1	t	ı	ì	71.7"	67.6	67.1	67.7	66.69	68.0	68.4	68.9	70.6	70.4	70.0	69.5
1/28	Fri	(Ced(h)	dBA	68.3	64.7	64.0	64.3	67.1	70.6	69.8	67.8	1	1	ı	1	ı	t	1	1	1	t	1	1	t	1	1	1
1/27	Thu	Leq(h)	dBA	1			1		1		1	1	68.2	68.3	68.8	70.0	69.3	69.3	68.8	68.9	68,9	69.0	69.3	9'69	69.7	69.5	67.7
1/25	Tue	Leg(N)	dBA	65.2	63.7	63.2	64.3	67.0	70.2	69.6	68.7	68.8	69.1	68.9	66.69	69.3	68.0	68.3	69.0	68.7	67.9	68.3	0.69	ı	1	1	1
1/24	Mon	Leq(h)	dBA	1	1	1	-		*		1	1	ı	1	t	1	1	1	1	69.3	68.9	68.9	69.6	69.3	689	68.7	67.1
22	**	_		am	am	am	arm	me	Bm	me	am	am	am	me	me	md	md	md	Ed	md	ш	ш	Ed	md	md	md	md
Date	Day:		TIME	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	00:6	10:00	11:00	12:00
				2:00 -	1:00 -	2:00 -	3:00 -	4:00	5:00 -	6:00	7:00	8:00 -	9:00	00:00	1:00	2:00 -	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	0:00	1:00


= Nighttime period

= No measurement, or rainy or wet period
 = Non-traffic related noise

Bold exceeds extraordinary abatement criteria

PROJECT: Building Acou Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	6T	DATE: 01-24-05
TOO Midfield Aven	ue,			SITE NO.: 7600
SOUND LEVEL METER: LD-870 LD-820 NL-31 LD-812 LD-2900	MICROPHONE: I NON-POLAR X POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: DE LD-900B LD-828	NOTES: SYSTEM PWR: BAT	
SERIAL #:	SERIAL #: 284163	SERIAL #:	(OBSERVATIONS AT START	
CALIBRATOR:	Celibration, dB: Input Reading Before 114.0 / 113.9	1550 1010	TOWARD (DIR): R. HUMIDITY: 1 % CAMERA E.T	MPH -
METER SETTING: A-WTD, SLOW RESPOR LEQ, Lo1, L10, L25, L50, I	NSE, 1 HOUR INTERVALS L90, LMIN, LMAX		PHOTO NOs. #3	

ST	ART	NOTES:
DATE	TIME	5.5 word force surrands patro - 2nd barrier
01-24-08	1600	\$,51 word force a propertyline includes 21 lattice at top
ST	TOP	covered muniphrane 425 1930 uncovered microphrane 427 0530
DATE	TIME	Desprey temporal part () 1/20 mm
DATE	TIME	Parenter transferred to the state of the sta



= Highest Messured Level

74.3 dBA

Hourly Noise Levels, Leq(h)


7606 Midfield Avenue, Inglewood, CA Rear Yard Location:

Position:

1-405 Highway Traffic Sources:

Date:

See attached Noise Measurement Form Notes:



74.3 dBA = Highest Measured Level

Hourly Noise Levels, Leq(h)

Location: 7605 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

Date: 1/24-1/31

Notes: See attached Noise Measurement Form

Rain occurred all day Wed, 1/25/05; no data reported.

1/31	Mon	Leg(h)	GBA	69.6	67.2	66.5	67.8	70.6	74.0	73.8	71.7	71.4	72.1	71.8	71.6	72.0	72.7	72.9	71.9	72.1	73.1	72.9	73.1	73.7	1	1	1
1/30	Sun	Leg(h)	dBA	71.3	70.1	9.69	67.5	67.4	69.1	70.9	71.6	72.4	73.2	73.6	73.0	71.2	7.07	70.6	7.07	71.6	71.8	71.9	73.4	74.1	73.8	73.0	71,8
1/29	Sat	Leq(h)	dBA	1	1			1			1	1	1	1	1	71.2	71.4	70.8	71.2	72.5	71,4	72.0	73.5	74.3	74.1	73.6	73,1
1/28	Fri	Leq(h)	dBA	69.7	67.9	67.3	67.4	70,1	73.9	73.2	71,3	1	1	.1	t	3	1	1		1	E	1	1	1	1	1	1
1/27	Thu	Leq(h)	dBA	1	1	1	1	1	1		1	1	71.8	72.0	72.4	73.6	73.0	73.0	72.5	72.6	72.6	72.8	73.0	73.4	73.5	73.1	71.2
1/25	Tue	Leq(h)	dBA	68.4	66.8	66.3	67.4	70.1	73.6	73.1	72.3	72.2	72.3	72.2	73.4	72.9	71,6	72.0	72.7	72.5	71.7	72.2	73.5	:	1		1
1/24	Mon	Leq(h)	dBA	1	1	1	1	ı	1		1	ı	1	1	ı	1	1	1	1	72.9	72.4	72.4	72.9	72.7	72.3	72.0	70.4
H	**	_	-	am	Es	Es	E	me	Bm	E	Eg	E	EB	E	E	Ed	E d	E d	Ed	Ed	E	md	md	Ed	Ed	md	md
Date	Day:		TIME	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00
		8				(4)			2.0																	13.	11:00 -


= Nighttime period

- a No measurement, or rainy or wet period

Bold exceeds extraordinary abatement criteria

PROJECT: Building Acou Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	ET	DATE: 01-24-05
7606 Midfield Aven	ue,			SITE NO.: 7606
SOUND LEVEL METER: LD-870 LD-820 LD-812 LD-2900	MICROPHONE: 12 NON-POLAR S POLARIZED 1/3-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: LD-900B	SYSTEM PWR: M BAT	
SERIAL#:	SERIAL #: 2141	SERIAL#:	TEMP: 4 PF	OF MEAS.)
CALIBRATOR:	Calibration, dB: Input Reading Before 114.0 / 114.0 After 114.0 / 114.0	1245- 1245-	TOWARD (DIR): R. HUMIDITY: U4 % CAMERA ET	MPH
METER SETTING: A-WTD, SLOW RESPO! LEQ, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS Leo, LMIN, LMAX		PHOTO NOs. #4,5	_

ny five fence	not fence mi	21 top section of ph	TIME NOTES:	START DATE TIM
but on message		Statem Site #	W W I DATA	STOP
coffee "	(Marchaele)	ierophone 1/25 19	TIME crucy	DATE TIM
Cooffee	N ADDRESS OF THE SECOND		TIME	DATE TIM



= Highest Measured Level

72.5 dBA

Hourly Noise Levels, Leq(h)

Location: 7612 Midfield Avenue, Inglewood, CA


Position: Rear Yard

Sources: I-405 Highway Traffic

Date: 1/24-1/31

Notes: See attached Noise Measurement Form

Rain occurred all day Wed, 1/26/05; no data reported. Automatic run timer stopped meter on Sunday at 12 noon.



Location: 7612 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24 - 1/31 Date:

72.5 dBA = Highest Measured Level

See attached Noise Measurement Form Notes:


		1/25 Tue Leght	1/24 1/25 1/27 Mon Tue Thu Thu Lea(h) Lea(h) dBA dBA dBA dBA
0.70	0.70		
65.4	65.4		
64.8	64.8	1 64.8	am + 64.8
69.9	65.9	69:0	am 65.9
68.5	68.5	68.5	am 68.5
72.0	72.0	72.0	
			71,0
_	_	71.0	71.0
			71.1
		70.9	70.9
		71.9	71.9
71.3 72.0	_	71.3	71.3
_	_	70.1	70.1
_	_	70.5	70.5
_	_	70.9	70.9
_	_	70.8	71.3 70.8
_	_	70.0	70.9
_	_	70.6	70.8
		72.2	71.4 72.2
			71.2
		1	70.9
1	100	1	70.8
1		0.69	


^{* * =} Non-traffic related noise - Nightlime period

⁼ No measurement, or rainy or wet period 1 *

Bold exceeds extraordinary abatement criteria Automatic run timer stopped meter on Sunday at 12 noon.

PROJECT: Building Acou Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER;	Bay and Mary	DATE: 01-24-05
TOCATION: 7612 Midfield Aven	ue,	•	The same	SITE NO.: 7612
SOUND LEVEL METER: □ LD-870 □ LD-820 □ NL-31 □ LD-812 □ LD-2900 □	MICROPHONE: I NON-POLAR ID POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: □ LD-900B □ LD-828 対 / 사사 - スト	SYSTEM PWR: A BAT	
CALIBRATOR: CALIBRATOR: CALIBRATOR: CALIBRATOR: CALIBRATOR: AND CA250 MARK 4155	Calibration, dB: Input Beading Before 93.8 / 93.9 After 93.8 / 93.8	1:00 10:36	TOWARD (DIR): Free a	MPH Grc4
METER SETTING: A-WTD, SLOW RESPON LEO, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS Leo, LMIN, LMAX		PHOTO NOs.	





74.3 dBA = Highest Measured Level

Hourly Noise Levels, Leq(h)


7616 Midfield Avenue, Inglewood, CA Location:

Rear Yard Position:

1-405 Highway Traffic Sources:

Date:

See attached Noise Measurement Form Notes:



74.3 dBA = Highest Measured Level

Hourly Noise Levels, Leq(h)

Location: 7516 Midfield Avanua, Inglewood, CA

Position: Rear Yard

1-405 Highway Traffic Sources:

1/24-1/31 Date:

Notes: See attached Noise Messurement Form

Rain occurred all day Wed, 1/26/05; no data reported.

1/30																										State of the last	
1/29	281	Leq(h)	GBA		1	1	,		1	1	1	1	1	1	1	71.9	72.3	7.17	71.9	73.0	7.1.7	72.2	73.5	74.1	73.9	73.5	72.8
1/28	LI.	Leq(h)	dBA	70.1	68.2	67.9	67.9	70.4	74.0	73.7	71.9	1	1	1	:	1	t	1	t	1	1		t	:	1		1
1/27	Thu	Lea(h)	dBA	1	1		1	1			1	t	72.7	73.0	73.4	74.3	73.7	73.7	73.2	73.1	72.9	73.2	73.4	73.8	73.9	73.3	71.8
1/25	Tue	Leg(h)	dBA	68.9	67.4	66.7	67.7	70.4	73.8	73.7	73.1	73.0	73.1	73.2	74.0	73.6	72.7	72.9	73.3	73.1	72.2	72.7	73.2	ı	1		
1/24	Mon	Legiti	dBA		1	1	1	1	1	1	ı	1	1	ı	1	1	1	1	1	73.4	73.0	72.8	73.3	73.2	72.8	72.5	70.7
36			1	mm mm	Ea	ma	me	me	ma	Bm	me	BITT	me	E	ma	ша	E d	md	Ed	End	Ed	Ed	Ed	Ed	Ed	md	ma
Date:	Day	-	IME	1:00	2:00	3:00	4:00	5:00	9:00	7:00	8:00	9:00	10:00	11:00	12:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00
				2:00 -	1:00	2:00 -	3:00 -	4:00 -	5:00 -	6:00 -	7:00 -	8:00 -	- 00:6	- 00:0	1:00 -	2:00 -	1:00	2:00 -	3:00 -	4:00 -	5:00 -	6:00	7:00 -	8:00 -	9:00	- 00:0	1:00 -


= Nightlime period

- = No measurement, or rainy or wet period

Bold exceeds extraordinary abatement criteria

PROJECT: Building Acous Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	larguer	DATE: 01-24-05
T616 Midfield Aven	ue,			SITE NO.: 7616
SOUND LEVEL METER: LD-870 LD-820 NL-31 LD-812 LD-2900 LD-812	MICROPHONE: NON-POLAR POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: LECTORER LD-828 LD-900C	NOTES: SYSTEM PWR: BAT	E) AC
SERIAL #:	SERIAL #: 19161 82	SERIAL#:	(OBSERVATIONS AT START	
CALIBRATOR:	Calibration, dB: Input Reading Before 14.0 / 5.864 After 14.0 / \\4.0		WIND SPEED: 0.6 TOWARD (DIR): NC R. HUMIDITY: 75 % CAMERA CANON A7 PHOTO NOs. 23 - 28	
METER SETTING: A-WTD, SLOW RESPON LEQ, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS		PHOTO NOs. 23 - 28	

ST	ART	NOTES: Acution equipment @ Freeway level/storage
DATE	TIME	(Angress) of the second
01-24-05	13:26:00	gard morophone (resident) YES 2025 uncovered manphone oftos
3"	TOP	chind migraphine (verdence) LES 5052 augusti mushing plas
DATE	TIME	



70.5 dBA = Highest Measured Level

Hourly Noise Levels, Leq(h)

Location: 7620 Midfield Avenue, Inglewood, CA


Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24 - 1/31

Notes: See attached Noise Messurement Form

Rain occurred all day Wed, 1/26/05; no data reported. Automatic run timer stopped meter on Sunday at 4 pm.



Location: 7620 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Trafflo

1/24 - 1/31 Date:

70.5 dBA = Highest Measured Level

Rain occurred all day Wed, 1/26/05; no data reported. See attached Noise Measurement Form Notes:

1/31	Mon	Leg(h)	dBA			*	THE PARTY NAMED IN	*				•						٠			•	*	•		t	1000	
1/30	Sun	Leg(h)	dBA	66,5	65.5	64.6	62.6	62.7	64,3	66.1	68.7	67.1	87.8	68,0	67.4	66.2	84.8	64.8	84.9								
1/29	Sat	Leq(h)	dBA	+		1	*	-	1	1	ı	1	ı	ı	1	66.8	68.3	65.5	66.8	68.7	67.4	68.0	69.8	70.5	70.2	69.5	68.8
1/28	Fri	Leq(h)	dBA	64,6	62.7	62.0	62.1	64.5	68.2	67.5	65.5	1	1	t	1	1	1	1	1	ı	1	1	1	1	ı	-	t
1/27	Thu	Leg(N)	dBA	1	1		1	1	1	1	1	1	67.1	68.1	66,8	68.0	67.2	67.2	999	69.9	67.2	67.7	67.7	68.0	68.4	67.6	68.0
1/25	Tue	Leq(t)	dBA	63,1	61.9	61,3	62.3	64.8	68.1	67.7	699	66.6	68.7	66.5	67.7	67.2	82.9	66.4	66.8	6.89	66.2	67.0	67.1	1	1	1	1
1/24	Mon	Leath	dBA	1					1		1	1	t	1	1	ı	1	1	1	67.3	67.1	67.1	67.1	67.0	66.7	68.6	65.1
17	9.0	-		me	am	am	me	me	me	me	me	me	Es	am	E	md	Ed	End	Hid	md	md	End	ш	md	md	md	md
Date	Day:		-	18	1:00 - 2:00	*	.+					,					,				*					*	11:00 - 12:00

= Nightfirms period

= No measurement, or rainy or wet period

. .

Bold exceeds extraordinary abatement criteria Automatic run timer stopped meter on Sunday at 4 pm.

PROJECT: Building Acou Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	dy and	Marr	DATE: 01-24-05
LOCATION: 7620 Midfield Aven	ue,		7	P MAL	SITE NO.: 7620
SOUND LEVEL METER: LD-870 LD-820 LD-812 LD-2900	MICROPHONE: NON-POLAR D POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: LD-900B LD-828 KNH-21	NOTES: SYSTEM PV		
CALIBRATOR: □ LD CA250 □ LK 4155	Calibration, dB: Input Reading Before 93,8 / 93,9 After 93,8 / 93,8	SERIAL #: O1530 TIME: 1(: 46 10:53	(OBSERVATIO TEMP: 76 WIND SPEED TOWARD (DI R. HUMIDITY CAMERA PHOTO NOs.	R):	OF MEAS.)
START NO DATE TIME 01-24-05 [2:00 STOP DATE TIME	Bag on - Toes	off on	Wed	Back	ou fn
1-30-05 12:00	19' 19'	wood t	4 9'-	1	5'-10"

= Highest Measured Level

68.8 dBA

Hourly Noise Levels, Leq(h)


7626 Midfleld Avenue, Inglewood, CA Rear Yard Location:

Position:

1-405 Highway Traffic Sources

Date:

See attached Noise Messurement Form Notes:



Location: 7625 Midfield Avenue, Inglewood, CA Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24-1/31 Date:

68.8 dBA = Highest Messured Level

Rain occurred all day Wed, 1/28/05; no data reported. Notes: See attached Noise Measurement Form

1/31	Mon	Leg(h)	dBA	62.7	60.3	59.5	60.7	63.4	66.7	66.2	64.1	63.8	64.5	64.1	64.0	64.3	65.1	65.4	64.3	64.5	66,4	68.4	68.4	67.1	1	1	1
1/30	Sun	Leg(h)	dBA	64.2	63.4	62.3	60.2	60.5	62.0	63.9	64,4	64.9	85.5	66.2	65.6	64.1	62.7	64.8	62.9	64.2	65.8	65.0	68.4	67.6	67.0	66.0	65.1
1/29	Sat	Les(h)	dBA	1		1		1			:	1	1	1	t	66.3	62.9	64.5	65.0	67.4	65.5	66.2	68.2	68.8	68,4	67.6	67.0
1/28	Fri	Leg(h)	dBA	62,4	9.09	9.69	59.8	62,4	68.3	86.3	63.2	1	1	t	1	1	1	t	1	1	1	1	1	1	1	-	
1/27	Thu	Leg(h)	dBA					1	1	1	1	ı	63,7	63.7	64.5	66.7	64.9	64.9	64,4	64.8	65.1	65.7	85.6	65.8	68,4	65.6	64,0
1/25	Tue	Legin	dBA	60.7	59.6	59.1	60.2	62.8	66.2	65.4	64.6	64.4	64.5	64.4	65.8	65.3	63.7	64.2	64.7	64.6	64.0	64.9	65.3	1	1	*	1
1/24	Mon	Leg(h)	dBA	1	,	1		1	1	1	1	t	1	i	1	t	1	1	1	65.4	65.0	65.1	65.0	64,9	64.5	64,4	63.0
¥	**	-		am	am	B.M.	Ee	ams	EE	me	ma	E	Est	E	E	md	Ed	Hd	Hd								
Date	Day:	1000000	TIME	1:00	2:00	3:00	4:00	5:00	8:00	7:00	8:00	9:00	10:00	11:00	12:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00
				12:00 -	1:00 -	2:00 -		22	50.											. *			- 7		9:00	100	160


= Nighttime period

- = No measurement, or rainy or wet period

Bold exceeds extraordinary abstement criteria

PROJECT: Building Acou Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	Volaric	DATE: 01-24-05
T626 Midfield Aven	ue,			SITE NO.: 7626
SOUND LEVEL METER: D LD-870 LD-820 NL-31 LD-812 LD-2900	MICROPHONE: □ NON-POLAR 5XPOLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: 27 LD-900B LD-828 2200	SYSTEM PWR: BAT	X AC
SERIAL #: 344	SERIAL #: 20 29	SERIAL #:	TEMP: 70 PF	OF MEAS.)
CALIBRATOR: CALIBRATOR: CALIBRATOR:	Input Reading	1050	TOWARD (DIR): VARA R. HUMIDITY: G3 % CAMERA 175	
METER SETTING: A-WTD, SLOW RESPON LEQ, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS L90, LMIN, LMAX		PHOTO NOs. 2	

DATE	-			
M751 64	TIME	comed mecrophone 1/25	1920	uncovered microphone " underestron
01-24-05	14:30			
STO				
DATE	TIME			



= Highest Measured Level

71.9 dBA

Hourly Noise Levels, Leq(h)


7634 Midfield Avenue, Inglewood, CA Rear Yard Location:

Position:

1-405 Highway Traffic 1/24 - 1/31 Sources:

Date:

See attached Noise Measurement Form Notes:



Location: 7834 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24-1/31 Date:

71.9 dBA = Highest Measured Level

Notes: See attached Noise Measurement Form

Rain occurred all day Wed, 1/26/05; no data reported.

		Leq(h) Leq(h)											_				_		-		_	_					199.7
1/29	Sat	Leg(N)	dBA	1			1	1		1	1	1	t	t	ı	67.9	69.2	68.9	68.3	68.6	67.5	68.0	69,4	70.4	70.3	70.2	69.8
1/28	Fri	Leq(h)	dBA	67.5	0.99	65.2	65.4	68.3	71,8	71.1	0.69	1	1	1	t	£	1	1	1	1	t	1	1	1	1		1
1/27	Thu	Leght	dBA			1	1			1	1	1	69,4	68.9	70.1	71.5	71.2	71.2	70.9	70.8	70.8	70.5	71.0	71.3	71.0	70.8	69.1
1/25	Tue	Log(h)	dBA	66.3	64.7	84,0	65.0	68.0	71.4	7.07	69.8	69.7	66.9	8.69	71.2	71.0	69.5	9.69	70.9	70.6	69.5	89.6	71.6	1	ı	1	1
1/24	Mon	Leght	dBA	1	1	1	1	1	-	1	1	1	1	1	1	ľ	1	ı	ı	7.07	70.2	669	77.1	70.8	70.4	8.69	68.1
	2*		-	am	Bm	me	E	me	me	me	am	E	me	me	E	md	md	E	Ed	Ed	End	Ed	Ed	Ed	md	md	ma
Date:	Day	1	TIME	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00
		100		2:00 -	1:00 -	2:00 -	3:00 -	4:00 -	- 00:9	- 00:9	7:00 -	8:00	9:00	- 00:0	1:00 -	2:00 -	1:00 -	2:00	3:00	4:00 -	5:00 -	9:00	- 00:2	8:00 -	- 00:6	00:0	1:00 -


= Nighttime period

- = No measurement, or rainy or wet period

Bold exceeds extraordinary abatement criteria

PROJECT: Building Acou Near I-405 in the	stical Study for Houses City of Inglewood, CA	LOO VO	zquez	DATE: 01-24-05
LOCATION: 7634 Midfield Aven	ue,			SITE NO.: 7634
SOUND LEVEL METER: LD-870 LD-820 NL-31 LD-812 LD-2900 L	MICROPHONE: [] NON-POLAR DEPOLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: LD-900B LD-828	NOTES: SYSTEM PWR: BA	
SERIAL #: A 11 77 CALIBRATOR: LD CA250 D METER SETTING:	SERIAL #: 16967 Calibration, dB: Input Reading Before 114.0 / 7.8 off After 114.0 / 113.9	SERIAL 8: 629 TIME: 4:31:20 125	(OBSERVATIONS AT STAF TEMP: PF WIND SPEED: TOWARD (DIR): R. HUMIDITY: S CAMERA(ANON)	_MPH
Control of the Contro	NSE, 1 HOUR INTERVALS L90, LMIN, LMAX		1	-46

S1	ART	NOTES:		14.00	to	1
DATE	TIME	Backyard	elevated	nelative	10	freeway
01-24-05	132144 46	The second secon	The second second second			1 1/2 24
	TOP	Counted wickers	have 1/25 07	18 unemered	MIC	mphre 1/27 2004
DATE	TIME	ale	on set off v	ne swetter befa	lana	into adobe expse 1145 L
		> a.e.	m 30. 411	d or old	00.57/10	idun!



= Highest Measured Level

71.6 dBA


Hourly Noise Levels, Leq(h)

7700 Midfleld Avenue, Inglewood, CA Rear Yard Location:

Position:

1-405 Highway Traffic 1/24 - 1/31 Sources:

See attached Noise Measurement Form Notes:



Location: 7700 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic Date: 1/24 - 1/31

71.6 dBA = Highest Measured Level

Rain occurred all day Wed, 1/26/05; no data reported. Notes: See attached Noise Measurement Form

1/30	Sun	Leghi	dBA	67.9	6.99	88.8	64.3	64.3	0.99	67.8	68.5	69.3	70.0	70.2	9'69	68.4	67.7	67.8 67.4 70.0	67.6	0.69	69.1	68.8	70.4	70.8	70.6	7.69	68.5
_									III SE			_	_	68.9	_	_	70.1	70.1	69.8	69.9	69.8	69.7	70.0	70.3	70.3	6.69	1 100
1/25	Tue	Leegh)	dBA	65.4	63.6	63.1	64.4	67.3	70.5	70.1	69.5	69.4	69.5	69.1	70.4	70.0	68.5	69.1	89.8	69.5	68.6	69.0	71.6	1	1	1	THE RESERVE THE PERSON NAMED IN
1/24	Mon	Leq(h)	dBA	1	1	1		1	1	1	1	ı	1	1	ı	1	1	1	1	669	69.4	69.3	70.1	69.8	69.4	68.9	87.0
Date:	Day:		TIME	8	00 - 2:00 am			18					- 10:00	- 11:00			- 2:00	2:00 - 3:00 pm	- 4:00		- 6:00		- 8:00	- 9:00	- 10:00	- 11:00	12-00


= Nightlime period

= No messurement, or rainy or wet period

Bold exceeds extraordinary abatement criteria

PROJECT: Bullding Acou Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	Jazquez	DATE: 01-24-05
7700 Midfield Aven	ue,	*		SITE NO.: 7700
SOUND LEVEL METER: LD-870	MICROPHONE: NON-POLAR [] POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: LD-900B LD-828	NOTES: SYSTEM PWR: □ BAT	
SERIAL #: OSSS CALIBRATOR: LD CA250 METER SETTING: A-WTD, SLOW RESPON	SERIAL #: 1785 Calibration, dB: Input Reading Before 114.0 / 21.2 of After 114.0 / 113.9		(OBSERVATIONS AT START TEMP: 11.0) °F WIND SPEED: 0.0 TOWARD (DIR): 1/0 R. HUMIDITY: 59 % CAMERA (ANON A PHOTO NOS. 15 - 2.2	мрн

PLATES.					-	married Oleman & Vac	A 70 EVA
DATE	TIME	I-405	Lepressed	LEVELIN	10	microphone los	AUT TO
01-24-05		Conered	microphone	425 1913	uncon	ed minophone 427 (3735
STOR	P			A COLUMN		A	
DATE	TIME						



68.3 dBA

Hourly Noise Levels, Leq(h)

7706 Midfield Avenue, Inglewood, CA Location:


Rear Yard Position:

1-405 Highway Traffic 1/24 - 1/31 Sources:

Date:

See attached Noise Measurement Form Notes:

Rain occurred all day Wed, 1/26/05; no data reported. A/C power failure on Sunday at 11 am.



Location: 7705 Midfield Avenue, Inglewood, CA

Position: Rear Yard

1-405 Highway Traffic Sources:

1/24-1/31 Date:

68.3 dBA - Highest Measured Level

Rain occurred all day Wed, 1/26/05; no data reported.

Notes: See attached Noise Measurement Form

1/31	Mon	Legin	dBA														,								1		1
1/30	Sun	Leq(h)	dBA	65.0	63.9	63.6	61.5	61.4	62.9	65.1	65,5	66.5	67.1	88.8												The state of the s	
1/29	Sat	Laq(h)	dBA	1	*	1	1	7	1		1	t	1	1	ı	63.8	64.0	63.5	64.3	699	65.0	65.8	67.1	68.0	87.8	67.2	68.9
1/28	F	Leq(h)	dBA	63.7	62,4	61.2	61.5	64.4	68.3	87.5	65.4		1	1	ı	1	1	t	1	1	t	1	ŧ	:	1	1	+
1/2/	Thu	Legiti	dBA		1	-	1	1	1	1	1	1	67.6	65.0	65.1	96.4	99.0	66.0	85.8	66.1	66.2	999	9.99	66.9	67.1	67.0	65.1
1/25	Tue	Leagh)	dBA	62.1	60.5	0.09	61.3	63.9	67.3	999	66.2	66.2	66.3	85.6	67.0	62.9	64,3	64.8	65.7	65.6	64.9	65,4	67.0	1	1	-	
1/24	Mon	Leg(h)	dBA	1	1	1		1	:	1	1	1	1	1	1	1	ı	1	1	66.1	65.9	699	68.6	66.1	65.7	65.6	64.1
17	**	-		me	me	me	ше	me	me	Eliz	me	E	E	me	me	md	Ed	md	md	Ed	md	Ed	Eld	Ed	Ed	md	md
Date	Day:		TIME	+						110			9:00 - 10:00		*											10:00 - 11:00	13


= Nighttime period

- No measurement, or rainy or wet period

= A/C power failure on Sunday at 11 am

PROJECT: Building Acou Near I-405 In the	stical Study for Houses City of Inglewood, CA	ENGINEER:	Т	DATE: 01-24-05
T706 Midfield Aven	ue,			SITE NO.: 7706
SOUND LEVEL METER: LD-870 LD-820 NL-31 LD-812	MICROPHONE: M NON-POLAR ID POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: M LD-900B LD-828	NOTES: SYSTEM PWR: BAT	
SERIAL #: 023\r	SERIAL #: 47451	SERIAL #:	TEMP: 64-9F	AND PROPERTY.
CALIBRATOR:	Calibration, dB: Input Reading Before 114.0 / 114.0 After 114.0 / 113.8	10:50A 19:05	TOWARD (DIR): R. HUMIDITY: 18 %	
METER SETTING: A-WTD, SLOW RESPO LEO, Loi, L10, L25, L50,	NSE, 1 HOUR INTERVALS Leo, LMIN, LMAX		PHOTO NOs.	=
DATE TIME	TES:			941 6

S	TART	NOTES:	
DATE	TIME		
01-24-05	11:00A		
8	ТОР		
DATE	TIME		
Tantal street			



68.2 dBA

Hourly Noise Levels, Leq(h)


7710 Midfield Avenue, Inglewood, CA Rear Yard 1-405 Highway Traffic 1/24 - 1/31 Location:

Position:

Sources:

Date:

See attached Noise Measurement Form Notes:



Location: 7710 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24-1/31 Date:

68.2 dBA = Highest Messured Level

Notes: See attached Noise Measurement Form

Rain occurred all day Wed, 1/26/05; no data reported.


1/31	Mon	Lesq(h)	dBA	63.2	61.0	80.0	61.3	64.1	67.3	67.4	66.6	66.6	65.4	84.9	64.7	65.1	65.8	86.2	65.4	65.4	86.5	66.5	66.7	67.1	1		
1/30	Sun	Ceq(h)	dBA	64.9	63.5	63.2	61.1	6'09	62,6	64,4	65.1	65.8	66.7	66.7	86,2	64.4	63.8	63.8	64.0	65.3	65.4	65.3	66.7	67.5	67.3	66.4	65.3
1/29	Sat	Leq(h)	dBA		1	1	1	1	1	1	1	1	1	1	1	64.3	64,6	64.1	64.8	1.99	65,4	1.99	67.3	68.2	87.8	67.1	67.0
1/28	Fri	Leq(h)	dBA	63.1	61.6	80.8	60.8	63.6	67.2	66.7	65.0	1	1	1	1	1	1	1	r	1	E	1	1	1	1	1	
1/27	Thu	Leg(h)	dBA	*	1	1	1	1	1	-	1	1	65,3	65.2	65,4	999	66.2	66.3	66.0	629	98.0	96.0	66.3	9999	66.7	66.3	64.6
1/25	Tue	Leg(h)	dBA	61.7	60.1	59,4	9'09	63.2	68.6	56.4	65.8	65.7	65.8	65.6	68.7	66.1	64.8	65.0	829	65.7	64.8	65.2	66.3	1	1	1	
1/24	Mon	Leq(h)	dBA	1	-	+					1	ı	1	1	ı	1	1	1	1	66.1	65.7	65,5	86.3	62.9	65.5	65,2	63,6
12	**			Bm	Ee	me	me	me	Ee	mu	me	E	E	E	E	Ed	Ed	Ed	Ed	End	md	ш	md	Ed	Ed	md	md
Date	Day:	100000000000000000000000000000000000000				14.1				1.0															- 10:00		
				12:00	1:00	2:00	3:00	4:00	5:00	8:00	7:00	8:00	9:00	10:00	11:00	12:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00

= Nightlime period

No measurement, or rainy or wet period

PROJECT: Building Acous Near I-405 in the	stical Study for Houses City of Inglewood, CA	LOC V	024022	DATE: 01-24-05
T710 Midfield Aven	ue,			7710
SOUND LEVEL METER: LD-870	MICROPHONE: LI NON-POLAR POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: LD-900B LD-828	SYSTEM PWR: BAT	
SERIAL #:	SERIAL #: 2145280	8ERIAL #: 0 225	TEMP: 65.3 F	- 7
CALIBRATOR:	Calibration, dB: Input Reading Before 14.0 / 9.1 df After 14.0 / 13.8	11:24:00 11:45	WIND SPEED: 0 TOWARD (DIR): 100 R. HUMIDITY: 73 % CAMERA (Anon A PHOTO NOS. 9-14	
METER SETTING: A-WTD, SLOW RESPON LEG, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS L90, LMIN, LMAX		PHOTO NOs. <u>9-14</u>	

ST	ART	NOTES:
DATE	TIME	Sprinkler system non-operational For years.
01-24-05	11:24	covered morophone 1/25 1909 unconned microphone 457 0900
51	гор	
DATE	TIME	



dBA

68.8

Hourly Noise Levels, Leq(h)


7716 Midfield Avenue, Inglewood, CA Location:

Rear Yard Position: I-405 Highway Traffic Sources: Date:

1/24-1/31

Notes:

See attached Noise Measurement Form Rain occurred all day Wed, 1/25/05, no data reported.



Location: 7716 Midfield Avenue, Inglewood, CA

Rear Yard Position:

Sources: 1-405 Highway Traffic

1/24-1/31 Date:

68.8 dBA = Highest Measured Level

See attached Noise Measurement Form Rain occurred all day Wed, 1/26/05; no data reported. Notes:

1/3	Mor	Leq(h)	dBy	64.3	62.	61.	62.	65,	68.	68	78.6	77.2	.99	68.0	85.	66.3	67.	67,	68.	68,	67.3	68.	68	68.	1	-	1
1/30	Sun	Leq(h)	dBA	65,8	64.6	64.2	62.2	62.1	63.6	65.5	66.1	68.9	67.8	67.8	67.1	65.2	64.8	64.6	64.9	66.2	66.4	66.5	67.9	68.6	68.4	67.5	68.4
1/29	Sat	Leghi	dBA	1	1	1			1	1	1	1	ı	1	t	65.5	85.8	65.1	65.6	67.0	66.3	688	68.0	68.8	68.6	68.0	67.7
1/28	Fri	Leq(h)	dBA	64.5	62.9	82.2	62.4	65.1	9'89	68,1	66.3	1	1	1	1	ı	1	ı	1	t	1	1	ı	1	t	1	
1/27	Thu	Leq(h)	dBA	4	1				1	1	1	1	68.7	66.5	66.8	68.0	87.8	67.5	67.3	67.2	67.4	67.5	57.7	67.9	68.1	87.8	629
1/25	Tue	Leg(h)	dBA	63.2	61.6	61.0	62.1	64.6	68,3	67.9	67.3	67.3	67.4	67.0	88,2	67.5	66.2	96.4	67.2	67.1	66.1	66.7	68.1	I	1	1	1
1/24	Mon	Leq(h)	dBA			1	1		ı	1	1	1	ı	1	1	1	1	1	1	67.5	67.2	67.3	67.8	67.3	69.9	66.6	65.0
22		_		am	me	Ee	am	am	mu	am	me	am	am	me	me	End	End	Ed	Ed	mud	Ed	Ed	md	md	md	md	md
Date	Day:	10000	TIME	1:00	- 2:00	- 3:00	4:00	5:00	- 6:00	7:00	8:00	9:00	10:00	11:00	12:00	1:00	2:00	3:00	4:00	9:00	00:9	7:00	8:00	00:6 -	10:00	- 11:00	12:00
			2000	2:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	00:00	1:00	2:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	00:0	11:00


= Nighttime period

= No measurement, or rainy or wet period

= Non-traffic related noise

PROJECT: Building Acous Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	e Volaric	DATE: 01-24-05
LOCATION: 7716 Midfield Aven	ue,			SITE NO.: 7716
SOUND LEVEL METER: LD-870	MICROPHONE: D HON-POLAR APPOLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: □ LD-900B □ LD-828 □ LD-828	NOTES: SYSTEM PWR: BAT	aç'ac
SERIAL #: 1190	SERIAL #:	SERIAL #:	TEMP: 66 "F	
CALIBRATOR: AQLD CA250	Calibration, dB: Input Reading Before 1/4 o 1/4 d After 1/4 0 1/4 d	TIME:	WIND SPEED: 1-21 TOWARD (DIR):	MPH E
METER SETTING: A-WTD, SLOW RESPON LEG, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS		PHOTO NOs. # 1/8	

ST	ART	NOTES:				50.1 /00 - 10 /00 /00 /00 /00
DATE	TIME	conered	microphene	1/25	1908	menond maryonne Yzz 0750
01-24-05	15:00		0			
ST	гор]				
DATE	TIME					



69.0 dBA


Hourly Noise Levels, Leq(h)

7722 Midfield Avenue, Inglewood, CA Rear Yard Location:

Position:

1-405 Highway Traffic 1/24 - 1/31 Sources:

See attached Noise Measurement Form Notes:



69.0 dBA = Highest Measured Level

Hourly Noise Levels, Leq(h)

Location: 7722 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

Date: 1/24-1/31

Notes:

 See attached Noise Messurement Form Hain occurred all day Wed, 1/26/05; no data reported.


1/31	Mon	[red(h)	dBA	64.7	62.6	81.6	62.9	65.7	68.9	68.7	67.1	9.89	66.7	66.1	629	88.4	67.3	67.7	66.9	699	68.1	68.0	68.4	68.7	1	1	
1/30	Sun	Leq(h)	dBA	66.2	65.1	64.7	62.7	62.4	64.1	699	9.89	67.3	68.1	68.0	67.5	65.5	64.9	64.6	65.0	66.5	66.7	66.7	68.2	69.0	68.8	67.9	6.99
1/28	Sat	Leg(h)	dBA		1	-	-	1	1	-	1	t	t	1	t	65.0	65.5	65.0	65,4	68.7	66.1	66.7	67.9	68.7	68.6	68,1	67.7
1/28	Fri	Laght	dBA	64,6	63.0	62.4	62.6	65,4	68,8	68.1	66.2	1	1	1	1	1	ı	1	1	1	1	1	1	1	1	1	1
1/2/	Thu	Leq(h)	dBA	1	1			1		-	1	1	999	66.2	86.4	67,8	67.6	67.6	67.4	67.4	67.5	67.6	67.8	68.0	68.3	67.8	66.2
1/25	Tue	[Leq(h)	dBA	63,4	62.0	61.2	62.3	65.1	68,4	68.0	67.2	67.2	67.3	67.1	68.3	87.8	66.0	66.3	67.2	67.2	66.4	68.7	67.1	ı	1	1	
1/24	Mon	Leq(h)	dBA	1		1	1	1	1	1	1	ı	1	ı	1	1	1	1	1	67.6	67.3	67.1	68.0	67.6	67.1	6.89	66.3
12				am	E	me	am	am	am	am	Es	E	ши	Es	шв	ELIC	Ed	md	End	md							
Date	Day:		F	- 1:00	13			- 5:00							+												
				2:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	00:00	1:00	2:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00

= Nighttime period

= No measurement, or rainy or wet period

PROJECT: Building Acou Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	Volaric	DATE: 01-24-05
LOCATION: 7722 Midfield Aven	ue,	39		SITE NO.: 7722
SOUND LEVEL METER: LD-870 LD-820 NL-31 LD-812 LD-2900 LD-812	MICROPHONE: NON-POLAR POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: LD-900B LD-828	SYSTEM PWR: BAT	□ AC
SERIAL #: /44	SERIAL #: 45108	SERIAL#:	TEMP: C7 PF	OF MEAS.)
CALIBRATOR: _P(LD CA250	Calibration, dB: Input Reading Before 114 / 114 After 114 / 114	15:53 12:10	WIND SPEED:	
METER SETTING: A-WTD, SLOW RESPO LEQ, L01, L10, L25, L50,	NSE, 1 HOUR INTERVALS L90, LMIN, LMAX		PHOTO NOs.	

ST	ART	NOTES: , 75			200
DATE	TIME	Conved nucrophene 2007	unconcrd	microphose 1/27	0428
01-24-05	16:00				
S	TOP				
DATE	TIME				



67.1 dBA

Hourly Noise Levels, Leq(h)

Location: 7726 Midfield Avenue, Inglewood, CA


Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24 - 1/31

Date:

Notes: See attached Noise Measurement Form



Location: 7728 Midfield Avenue, Inglewood, CA

Rear Yard Position:

1-405 Highway Traffic Sources:

1/24-1/31 Date:

67.1 dBA - Highest Measured Level

See attached Noise Measurement Form Notes:

Rain occurred all day Wed, 1/28/05; no data reported.


Mon	Leq(h)	61.6	59.7	58.7	60.09	62.7	86.8	69.9	64.2	63.2	83.2	62.4	62.1	62.3	63.0	63.8	63.1	63.3	64.6	64.8	65.0	65.6	1	t	1
Sun	Legh)	62.0	61.9	61.5	59.5	59.4	0,18	62.8	63.4	64.1	64.5	67.1	71.5*	63.3	63.4	61.7	61.4	63.4	63,5	63.5	65.2	65.8	65.7	84.8	63.8
1/29 Sat	Lea(h)	wan.							1	1	ı	1	ı	62.0	61.9	61,5	62.4	64,4	63.9	64,5	65.6	66.1	62.9	65.2	64.7
1/28 Fri	Leq(h)	82.1	60.7	59.9	60.1	62.9	66.2	65.4	64.7	1	t	1	1	ı	t	1	t	1	1	1	1	1	1	-	1.
1/27 Thu	Legitio	400		1	1		1	1	1	1	63.4	62.6	62.9	84.1	63.6	83.8	63.6	63.7	64,0	64.2	65.3	65,2	65.5	65.0	63.6
1/25 Tue	Leq(h)	AD 1	58.6	58.0	59.0	8,10	65.1	64.8	54,4	64.2	64.1	63.7	64.6	63.7	62.3	62.7	63.4	63.3	62.8	63.3	66.2	1	1	1	1
1/24 Mon	Leq(h)	dBA	1	1		i	1		1	1	t	1	1	1	1	ı	ŧ	64.0	63.9	63.9	84.8	64.2	63.7	63.6	62.0
11 -	_	arrest and	am	me	me	am	arm	arm	am	am	am	am	am	md	md	md	Ed	Ed	md	md	md	md	ша	Ed	md
Date:	-	- 18	1:00 - 2:00			*									*		+			+		*	*	*	

= Nighttime period

 No measurement, or rainy or wet period
 Non-traffic related noise. 1 *

PROJECT: Building Acou Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	Volaric	DATE: 01-24-05
T726 Midfield Aven	ue,			SITE NO.: 7726
SOUND LEVEL METER: LD-870	MICROPHONE: NON-POLAR PEPOLARIZED	PRE AMP: CLD-900B LD-828	NOTES: SYSTEM PWR: BAT	ESECULE.
SERIAL #: 0 17 CALIBRATOR: LD CA250 METER SETTING: A-WTD, SLOW RESPON	SERIAL #: 47475 Calibration, dB: Input Reading Before 114 / 114 After 114 / 113.9	SERIAL #: 3915 TIME: 2 15:30 1220	(OBSERVATIONS AT START TEMP:	OF MEAS.)
LEG, L01, L10, L25, L50, I	L90, LMIN, LMAX			

	RT	NOTES:
DATE	TIME	cound microphine Y25 1902 meneral microphone: windows.
01-24-05	15:38	Change
STO	P	
DATE	TIME	



65.0 dBA


Hourly Noise Levels, Leq(h)

7732 Midfield Avenue, Inglewood, CA Location:

Rear Yard Position:

1-405 Highway Traffic Sources:

See attached Noise Measurement Form Notes:



Location: 7732 Midfield Avenue, Inglewood, CA Position: Rear Yard

Sources: 1-405 Highway Traffic

1/24 - 1/31 Date:

65.0 dBA = Highest Measured Level

Rain occurred all day Wed, 1/26/05; no data reported. Notes: See attached Noise Measurement Form

1/31	Mon	Leq(h)	dBA	59,8	57.8	56.8	58,0	60,7	84.0	64.2	62,3	61.0	60.8	59.6	59.1	59.6	60.3	61.0	60.3	909	62.5	62.9	63.1	63.9	1	:	
1/30	Sun	Laq(h)	dBA	80.8	60.2	59.6	57.4	57.4	59.1	61.0	61.3	61.6	61.9	61.5	60.7	58.9	58.3	58.1	59.0	9.09	61.1	61.7	63,4	84.2	64.0	63.0	62,3
1/29	Sat	Leq(h)	dBA		1					1	ı	Е	ı	ı	t	60,2	59.5	58.8	60.3	62.9	62.7	63.6	64.5	0.50	64.6	63.5	63.2
1/28	Fri	Leg(t)	dBA	59.3	57.8	56.8	57.0	59.9	63.3	62.8	64.6	ı	1	1	1	1	1	1	1	1	t	1	Ŀ	1	1		1
1/27	Thu	Leq(h)	dBA	1		-	1	1	1	1	1	1	61.1	60.2	80.2	61.3	60.9	61.2	60.9	61.2	61.5	62.1	62.3	62.4	63.2	62.4	80.09
1/25	Tue	Leq(h)	dBA	57.5	56.1	55.3	56.4	59.3	62.8	62.6	62.2	61.9	61.7	61.0	61.7	909	59.4	59.8	60.5	60.5	0'09	80.6	62.3	1	1	*	1
1/24	Mon	Leq(h)	dBA	-	t	1		1	1	1	1	ı	t	t	:	1	1	ı		1	61.1	61.4	62.3	61.6	61.1	61.1	59.5
12		_	- 0.	вш	E	Elia	E	me	Eme	me	ше	E	Eg	me	E	md	End	Ed	md	Ed	md	Ed	Ed	Ed	md	md	md
Date	Day:	C. Control	TIME	1:00	2:00	3:00	4:00	5:00	8:00	7:00	8:00	9:00	10:00	11:00	12:00	1:00	2:00	3:00	4:00	5:00	6:00	7;00	8:00	9:00	10:00	11:00	12:00
				2:00 -	1:00	2:00 -	3:00 -	4:00	5:00 -	6:00 -	7:00 -	8:00	9:00	- 0000	1:00	2:00 -	1:00	2:00 -	3:00	4:00	5:00	9:00	7:00	8:00	- 000:6	- 0000	1:00


= Nightlime period

= No measurement, or rainy or wet period

:

PROJECT: Building Acous Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	arquer	DATE: 01-24-05
T732 Midfield Aven	ue,			SITE NO.: 7732
SOUND LEVEL METER: LD-870	MICROPHONE: I NON-POLAR POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: LD-900B LD-828	NOTES: SYSTEM PWR: BAT	
SERIAL #: 8139 2	SERIAL #: 49492	3753	TEMP: 65.5 *F	A STREET
CALIBRATOR: MLD CA250	Calibration, dB: Input Reading Before 1140 / 3.341 After 14 / 14.1	TIME:	WIND SPEED: 6.5 TOWARD (DIR): NE R. HUMIDITY: 75 % CAMERA (ANON A7	
METER SETTING: A-WTD, SLOW RESPON LEG, Lo1, L10, L25, L50, I	NSE, 1 HOUR INTERVALS L90, LMIN, LMAX		PHOTO NOs.	=,

DATE	TIME	aver cast stres			
01-24-05	16:45:2	5 comered mucrophyme 1/25	1902	univered	murophine; mle
STO					
DATE	TIME				



67.4 dBA

Hourly Noise Levels, Leq(h)


7736 Midfield Avenue, Inglewood, CA Location:

Rear Yard Position:

I-405 Highway Traffic Sources:

Date:

See attached Noise Measurement Form Notes:



Location: 7736 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

Date:

1/24 - 1/31

67.4 dBA = Highest Measured Level

See attached Noise Measurement Form Notes:

Rain occurred all day Wed, 1/26/05; no data reported.


Dat	Day:	COMMO	TIME		100	(14)		8.4	100	3 4								2:00 - 3:00								16	
	::	_		am	am	am	E	Bm	E	E	me	E	E	E	Es	End	E	Ed	Ed	md	Ed	E	E	Ed	md	md	md
1/24	Mon	Leg(ti)	dBA	1	1	1	1	1	1	1	1	1	1	1	1	ı	1	1	1	64.9	64.8	64.7	65.5	65.0	64.5	64,4	62.8
1/25	Tue	Leq(h)	dBA	60.8	59.3	58.5	59.3	62.3	65.8	82,8	65,3	65.2	64.9	64.5	65.5	64.7	63.5	63.8	64.6	64.5	63.9	64.7	65,4	1	t	1	1
1/2/	Thu	Leg(h)	dBA	1		1	1	1	1	1	1	ı	62.9	64.6	64.5	69.9	64.6	67.4	64.8	64.7	65.0	65.3	65.5	65.5	66,2	65.4	63.9
1/28	Fri	Leq(h)	dBA	82,3	60,5	7,93	59.8	62.5	66.0	65.6	64.2	1	1	:	:	:	ı		1	1	1	t	t	:	:	*	1
1729	Sut	Leq(h)	dBA		1	t	1	,		1	1	1	1	ı	1	63.7	63.7	63.0	64,3	86.1	65.4	66.0	0.99	65.8	65.4	64.5	63.9
1/30	Sun	Leq(h)	dBA	61,8	61.1	60.4	58.2	58.3	59.8	81,8	61.9	62.4	63.2	63.0	63.9	63.5	85.2	62.8	62.7	64.0	64.5	65.0	9.99	67.4	87.2	66.2	65.3
1/3	Mor	Legi	dB/	62.6	60.7	59.8	80.9	63.7	86.8	86.9	65.2	64.6	84.5	53.7	63.2	63.8	64,3	64.7	63.8	64.5	66.0	66.2	66.3	87.0	1	1	1

= Nighttime period

- a No measurement, or rainy or wet period

PROJECT: Building Acou Near I-405 in the	stical Study for Houses City of Inglewood, CA	ENGINEER:	ET	DATE: 01-24-05
LOCATION: 7736 Midfield Aven	ue,			SITE NO.: 7736
SOUND LEVEL METER: □ LD-870 □ LD-820 □ NL-31 □ LD-812 □ LD-2900 □	MICROPHONE: CI NON-POLAR M POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: DE LD-900B LD-828	NOTES: SYSTEM PWR: □ BAT	
SERIAL #: 0427	SERIAL #: 3410 69	3202	TEMP: 4 F	- 200
CALIBRATOR:	Calibration, dB:	1145 1305	WIND SPEED: D TOWARD (DIR): R. HUMIDITY: 19 % CAMERA PHOTO NOs. # 11,12	
METER SETTING: A-WTD, SLOW RESPON LEG, L01, L10, L25, L50,	NSE, 1 HOUR INTERVALS Leo, LMIN, LMAX		PHOTO NOs. # 11,12	_

ST	ART	NOTES:
DATE	TIME	L cenera - 2 plestos fruit run house
01-24-05	12 NON	
87	ГОР	installation: first Posteyard's chattered in beliegings - residents moving
DATE	TIME	at notreinal: yards cleaned of, no nexistants
		or vinding. Some property



64.3 dBA

Hourly Noise Levels, Leq(h)

7742 Midfield Avenue, Inglewood, CA Location:

Rear Yard Position:


Sources:

1/24 - 1/31

Date:

I-405 Highway Traffic

See attached Noise Measurement Form Notes:



Location: 7742 Midfield Avenue, Inglewood, CA

Position: Rear Yard

Sources: 1-405 Highway Traffic

Date: 1/24 - 1/31

64.3 dBA = Highest Measured Level

Notes: See attached Noise Measurement Form Rain occurred all day Wed, 1/25/05; no data reported.


1/28 1/29 1/30	Fri Sat Sun	Leq(h) Leq(h) Leq(h) Leq(h)	dBA dBA dBA	58.0	57.3 - 57.2	56.1 - 56.3	56.4 - 54.2	59.5 - 54.5	62.9 - 56.9	62.4 - 57.9	61.7 58.2	58.5	- 59.2	688	1 29.5	60.8 58.7	59.8 58.3	59.0 58.1	60.8 58.6	- 64.1 60.3	63.6 60.7	64.3 61.5	64.3 63.0	64.2 63.8	- 63.3 63.7	+ 61.6 62.5	
1/25	Tue	Leq(h)	dBA	8,99	55.3	54.5	55.5	58.5	61,9	81.9	61,6	61,3	61.3	80.8	61,2	80.3	59,3	59.5	60.2	60.1	59.6	80.3	60.4	1	:	-	
1/24	Mon	Leng(h)	dBA	1		1	1	1	1	1	1	ı	t	1	1	1	1	1	1	80.8	60.7	60.9	61.8	61.1	80.6	60.5	
22	**		-	me	Es	me	Eg	E	am	me	Ele	E	E	E	E	E d	md	md	E d	Ed	md	ш	ш	Ed	md	Ed	
Date	Day:	100000000000000000000000000000000000000	TIME	- 1:00	- 2:00	- 3:00	- 4:00	- 5:00	- 6:00	7:00	8:00	- 9:00	- 10:00	11:00	. 12:00	1:00	- 2:00	3:00	- 4:00	- 5:00	- 8:00	- 7:00	- 8:00	- 9:00	- 10:00	- 11:00	
				12:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	00:01	11:00	2:00	1:00	2:00	3:00	4:00	5:00	8:00	7:00	8:00	9:00	00:01	

= Nightlime period

- = No measurement, or rainy or wet period

PROJECT: Building Acoustical Study for Houses Near I-405 in the City of Inglewood, CA		ENGINEER: Joel Nazque 2		DATE: 01-24-05
LOCATION: 7742 Midfield Aven	ue,			SITE NO.: 7742
SOUND LEVEL METER: LD-870 LD-820 NL-31 XLD-812 LD-2900 L	MICROPHONE: MICROPHONE: MICROPHONE: POLARIZED 1/2-INCH RANDOM INCIDENCE W/ WIND SCREEN	PRE AMP: D LD-900B D(LD-828	SYSTEM PWR: K BAT	□ AC
SERIAL #: 0639	SERIAL #:	SERIAL #:	(OBSERVATIONS AT START TEMP: 39.2 °F	OF MEAS.)
The state of the s			WIND SPEED: 1.2 TOWARD (DIR): N.E R. HUMIDITY: 82" % CAMERA CANON A	7.5
METER SETTING: A-WTD, SLOW RESPON LEQ, L01, L10, L25, L50, I	NSE, 1 HOUR INTERVALS L90, LMIN, LMAX		PHOTO NOs. 1-8	=

\$1/	MIT	NOTES:
DATE	TIME	Off ramp behind & sound wall
01-24-05	- 2-11-11	(2) double came windows - 2 nd floor, N-FALACE
51	OP	(2) " " - " ", 5- Focade
DATE	TIME	could missiphone 1/25 2012 mound wroppine 1/27 0740
		Instrument beg open, untoped



APPENDIX E

Instrumentation Calibration Log

LD 820 SLM	Cal-Date	Cal-Due Date
A1177	10/29/2004	10/29/2005

LD 812 SLM	Cal-Date	Cal-Due Date
A0639	6/15/2004	6/15/2005

LD 870A SLM	Cal-Date	Cal-Due Date
A0120	11/18/2004	11/18/2005
A0124	11/19/2004	11/19/2005
A0128	5/10/2004	5/10/2005
A0144	2/2/2004	2/2/2005
A0158	11/29/2004	11/29/2005
A0159	11/29/2004	11/29/2005
A0160	3/16/2004	3/16/2005
A0161	4/2/2004	4/2/2005
A0162	2/11/2004	2/11/2005
A0163	2/11/2004	2/11/2005
A0344	11/10/2004	11/10/2005
A0496	1/30/2004	1/30/2005
A0555	2/10/2004	2/10/2005
B1502	11/29/2004	11/29/2005

LD 870B SLM	Cal-Date	Cal-Due Date
B1047	1/17/2005	1/17/2006
B1190	1/17/2005	1/17/2006
B1392	1/17/2005	1/17/2006

LD 2900 RTA	Cal-Date	Cal-Due Date
A0236	10/10/2004	10/18/2005
A0427	2/18/2006	2/18/2006
A0484	10/30/2002	10/30/2003

Rion NL-31 SLM	Cal-Date	Cal-Due Date
110021	6/14/2004	6/14/2005
110030	9/3/2004	9/3/2005
610323	11/29/2004	11/29/2005
610336	11/10/2004	11/10/2005
610346	1/13/2004	1/13/2005

B&K 4230 Calibrator	Cal-Date	Cal-Due Date
542424	11/29/2004	11/29/2005

LD CA250 Calibrator	Cal-Date	Cal-Due Date
2479	5/12/2004	5/12/2005
2480	2/2/2004	2/2/2005